



SCS-7153 版本: 1

## HUBBLE Varifocal IP Network Camera, 3百萬像素, H.265, 802.3af PoE

The LevelOne SCS-7153 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for indoor IP surveillance networks. Offering clear, sharp imagery with 3-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne SCS-7153 should be an essential part of any security deployment that requires smart, reliable indoor cameras.

### Key Features

- 300 萬高畫質解析度
- 視頻壓縮格式: H.264, H.265, MJPEG
- Auto Back Focus (ABF) enhances camera functionality
- P-iris 自動光圈可自動調整光線 提供高品質影像畫面
- 具備WDR(寬動態)功能，在極亮或極暗的環境中也可提供清晰影像
- 支援3視訊以上串流
- 數位輸入/輸出(1DI/1DO) 可接感應器與警報設備
- 內建 Micro SD/SDHC 卡插槽

### 產品規格

#### 系統規格

標準和通訊協定:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

影像感測器:

1/2.8" Progressive CMOS

鏡頭:

Vari-focal Lens with F4 - 9mm / F4 - 10mm, P-Iris

連接埠:

1 x RJ-45 10/100/1000 Mbps PoE port Power Connector

1 x MicroSDHC/ MicroSDXC card slot

1 X RS-485, Terminal block

1 x Audio in/Out

1 x DI/DO

1 X build Microphone

1 x DC12V / AC24V

按鈕:

Reset button

指示燈號:

Power

紅外線濾片:

Removable infrared-cut filter for day & night function

快門時間:

1 ~ 1/10,000 sec (manual mode); 1 ~ 1/10,000 sec (auto mode)

視角:

CS Mount lens

影像壓縮技術:

H.265, H.264, MJPEG

解析度:

30 fps at 2065 x 1553

30 fps at 1920 x 1080

30 fps at 1280 x 960

30 fps at 1280 x 720

30 fps at 800 x 600

30 fps at 640 x 480

30 fps at 320 x 240

輸出影像格式:

RAW

音頻壓縮技術:

G.711

電源輸入:

DC 12V/0.6A Terminal block

PoE (802.3at)

電源消耗:

DC 12V/7W; PoE Class 3 (IEEE802.3af)/12.9W

資料傳輸率:

128 Kbps -20 Mbps (per stream)

存儲容量:

MicroSDHC / MicroSDXC memory card slot (card not included), up to 64GB

## 功能

一般:

Video motion detection (3 regions); External device through digital input; Sound detection; Tampering detection

PoE:

PoE Class 3 (IEEE802.3af) / 12.9W

安全性:

One-key Reset, Heartbeat, Password Protection, Change camera settings; Command other devices; E-mail notification with snapshots;

Save video or snapshot to local storage; Upload video or snapshot to FTP server; Activate external device through digital output

影像:

P-Iris; Wide Angle

Extreme WDR (118 dB);

White balance: automatic;

Brightness; Defogging; Contrast; Sharpness (auto);

Auto gain control; 2D+3D digital noise reduction;

Flickerless; Digital Image Stabilizer; 30 fps at 2720 x 1536;

音頻:  
8kHz, Mono; G.711

## 效能

訪問數:  
16

幀速率:  
30 fps at 2065 x 1553  
30 fps at 1920 x 1080  
30 fps at 1280 x 960  
30 fps at 1280 x 720  
30 fps at 800 x 600  
30 fps at 640 x 480  
30 fps at 320 x 240

最低照度:

Color: 0.04 lux at F1.4;  
B/W 0.002 lux at F1.4 (AGC on)

## 環境

溫度:  
10°C ~ 50°C (14°F ~ 122°F)

濕度(非冷凝):  
10% ~ 90% RH

## 物理規格

尺寸:  
52 x 82 x 150 mm

重量 (g):  
395 g

顏色:  
White

## 認證

電磁認證:  
CE/FCC

其他:  
ONVIF , Profile S conformant

## 其他

適用作業系統:  
Windows 7,8,10

相容性:  
IE 9 above

---

**Order Information:** SCS-7153

## Package Contents

SCS-7153  
資源光碟(使用說明書, 工具程式, 64-CH 監控軟體)

---

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.