



Megapixel PIR Lighting PoE Network Camera



FCS-0031


H/W Version: 1

LevelOne FCS-0031 is a fixed day camera with super image quality for home security and surveillance. It provides a distinct and stylish exterior mount unit with excellent features and quality, allowing plenty support of applications and wide area of coverage. Users can view the live motion image anywhere through web browser via the Internet. With the megapixel progressive sensor and white LED, FCS-0031 comes with high resolution quality and sharp sensitivity - a perfect solution for securing your home and office.

In addition, the FCS-0031 provides many advanced features, including human detection sensor (PIR),

Micro SD card slot and Privacy button. The FCS-0031 complies with 802.3af PoE standard and supports flexible deployment, even in locations without power outlet.

With an "Easy Installation Wizard", this LevelOne IP camera is very user-friendly, perfect for both home and business use. It is also embedded with a high-performance image sensor and CPU. The FCS-0031 supports H.264, MPEG4 and MJPEG video compression, providing a high resolution at 640x400 or 1280x800 for high-quality video and real-time viewing.



Key Features

- Megapixel (1280 x 800) high-definition resolution
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Built-in PIR sensor for human temperature detection
- Built-in white LED for auto-illuminating motion detected area
- Built-in microphone and speaker for 2-way audio communication
- Easy Internet monitoring via configuration free Level1DNS™ service
- Compression: H.264/MPEG-4/MJPEG
- Simple audio/video on/off with one-push Privacy Button
- Built-in Micro SD/SDHC card slot for local storage
- Free 64-channel monitoring software included (supports iCamSecure App)

Works Well With



FSW-0503
4FE PoE + 1 FE Switch




POI-2002
PoE Injector

Technical Specification

Camera
Image Sensor 1/4" Megapixel Progressive Scan CMOS
Effective Pixels 1280x800
Lens Board lens, fixed-focal, f=3.6 mm, F2.3
Angle of View (H) 55.7°
Minimum Illumination 1 lux (without LED) 0 lux (with LED)
Pan/Tilt/Zoom 4x Digital Zoom
Illumination LED Triggered by Auto PIR Sensor White LED distance up to 6m
Video
Video Compression H.264/MPEG4/MJPEG
Resolutions 1280x800 / 640x400 / 320x192
Frame Rate Up to 30 fps at all resolutions
Video Streaming Multiple simultaneous streams, up to 2 streams
Image Setting Adjustable image size, quality and bit rate Configurable brightness, sharpness, contrast, saturation, white balance and exposure AGC/AWB/AES Flip & Mirror Privacy Mask Time Stamp and Text Caption Overlay
Video Format Store to PC: .asf Store to SC Card: .mp4
Audio
Audio Streaming Two-way audio
Audio Compression G.711/AMR
Audio Input/Output Built-in microphone/speaker
Network
Networking 10/100 Mbps Ethernet, RJ-45
Security Multi-level user access with password protection IP address filtering HTTPS encrypted data transmission
Supported protocols TCP/IP, UDP, ICMP,DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP
Number of clients 10
DNS Easy Internet monitoring via configuration free Level1DNS™ service

Alarm and Event Management
Passive Infrared Sensor (PIR) PIR range up to 4m
Motion Detection 3 Detection Zones
Other Events PIR Detection
Notification HTTP, FTP, SMTP, Samba
General
Local storage MicroSD/SDHC card slot
Power DC12V 1A / 802.3af PoE
Power Consumption max. 4.1W
Connectors RJ-45 10BASE-T/100BASE-TX DC Power Jack
LED Indicator Power/Ethernet/Privacy
Button Privacy Mask Button Reset Button
Operating Temperature 0°C ~ 50°C
Operating Humidity 10% to 80%, non-condensing
Dimensions 34 x 70 x 105 mm
Weight 103g
Approvals CE, FCC
Viewing System Requirements OS: Microsoft Windows 7/Vista/XP Browser: Internet Explorer 6.x or above Cell phone: 3GPP player Real Player: 10.5 or above Quick Time 6.5 or above
Bundled Software Bundled with 64-Channel LevelOne IP CamSecure surveillance management software

Product Diagram



Order Information

Package Contents

FCS-0031: Megapixel PIR Lighting PoE Network Camera

- FCS-0031
- Power Adapter
- RJ45 Ethernet LAN Cable
- Quick Installation Guide
- CD Manual / Utility