



10/100Mbps Network Camera



FCS-1030

H/W Version: 2

Compact Sized Digital IP Network Camera

Have your home surveillance in your hand with the LevelOne FCS-1030 compact-sized IP network camera. It is able to broadcast live images to your handheld mobile phone or PDA and supports 3GPP/ISMA RSTP format via a 3G mobile phone.

This device is able to transmit optimal synchronized video and audio over the Internet thus provides the remote monitoring capabilities.


With a built-in web server, FCS-1030 provides an easy user interface for remote access to receive video signals from anywhere anytime over the Internet with the Internet Explorer browser.

DDNS is also configured to allow this camera to use an easier naming format to remember rather than an IP address.

Free bundled Surveillance Software

The FCS-1030 bundles with free software that allows the administrator to monitor up to 32 channels simultaneously.

This software supports even more features such as recording of streaming video directly to hard disk, enable motion detection and several video enhancement features, making this network camera an ideal solution to building a digital network-monitoring environment.



1. Status LED
2. Built-in Microphone
3. Power In
4. LAN Port

Key Features

- Live video and audio monitoring via 3G Mobile phone
- Optimal synchronization of audio & video
- Up to 30 frames per second in full VGA resolution
- Supports UPnP for Easy set-up and installation
- Motion detection
- Event-notification via E-mail
- Friendly GUI for easy configuration
- Free software included (Industry-leading 32-channel IP CamSecure Lite™ software)

Works Well With



FCS-9464
IP CamSecure Pro64 Mega




FCS-7011
1-Port PoE Video Server

Technical Specification

Network
Standards Compliance IEEE 802.3u
Ports 1 x RJ-45 10/100 Mbps port
Video
Compression Mode Stream Video (MPEG4) Still Photos (JPEG)
Max. Resolution 640 x 480
Frame Rate Up to 30/25 frames at 160 x 120 Up to 30/25 frames at 176 x 144 Up to 30/25 frames at 320 x 240 Up to 30/25 frames at 640 x 480
Still Picture JPEG
Video Record AVI
Camera
Sensor ¼" Color CMOS Sensor
Lens 4.0mm, F=2.0
View Angle Vertical 37° Horizontal 49°
Minimum Illumination 1.5Lux / F2.0
Electronic Shutter (Sec) 1/60 ~ 1/15,000 sec
AGC/AWB/AES
Audio
Microphone Omni-directional
Frequency 50 ~ 16000Hz
Audio Codec Algorithm GSM-AMR/MPEG4 AAC Supports audio mute
S/N Ratio More than 60dB
Digital Zoom 4x
Hardware & Environment
Flash ROM 4MB Flash ROM
SDRAM 32MB SDRAM
Housing Indoor use

Power Input: 100~240VAC, 50/60Hz, 0.4A Output: 5VDC, 2A
Temperature Operating: 0°C ~50°C (32 ~ 122)
Humidity Operating: 10%~95%(Non-Condensing)
Dimension 72.8mm(W) * 28.6mm(D) * 115.2mm(H)
Weight 215g
Supported Protocols IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, GMP, SMTP, FTP, DHCP, NTP, DNS, DDNS and PPPoE
Software Bundled with 32-Channel LevelOne IP CamSecure Lite surveillance management software
Viewing System Requirement
OS Microsoft Windows 2000/XP/Vista
Browser Mozilla, Firefox, Safari, Netscape, IE 6.x or above
3GPP Player Real Player 10.5 or above Quick Time 6.5 or above
EMI and Safety FCC, CE

Product Diagram



Order Information Package Contents

FCS-1030: 10/100Mbps Network Camera

FCS-1030
Power Adapter
Camera Stand
CD Manual/Utility
Quick Installation Guide