



2-Megapixel PoE Dome Network Camera



FCS-3071

H/W Version: 2

The LevelOne FCS-3071 is a compact H.264 2-Megapixel PoE Mini Dome Camera designed for tough environments. With its tamper-resistant and IP66-rated housing, it can withstand vibration, humidity, dust and fluctuating temperatures, makes it ideal for both indoor and outdoor applications, specifically designed for mass transit vehicles such as buses and trains. The FCS-3071 is an economical mobile surveillance solution with high reliability and performance, it utilizes PoE (Power-over-Ethernet) to power from a single Ethernet cable, giving greater ease of installation and cost saving. In order to facilitate onboard storage and data portability, the FCS-3071 is also complete with a Micro SD/SDHC card slot for local recording.

Exceptional Image Quality

With built-in 3DNR (3-Dimension Noise Reduction) and WDR (Wide Dynamic Range) technology, the camera is able to filter the intense backlight

surrounding a subject and remove noises from video signal. The result is that an extremely clear and exquisite picture quality can be produced even under any challenging lighting conditions.

64-channel Management Software

We aim to offer you the most versatile and comprehensive surveillance solutions. Our IP CamSecure software coming with the camera allows you to monitor up to 64 megapixel IP cameras simultaneously on one screen to enhance scalability. For added convenience and flexibility, the software includes various advanced features such as scheduling recording, event alert, and heaps more. In addition, simply install our free iCamSecure App to your smartphone and connect to the PC with IP CamSecure software installed, you will easily turn your iPhone/Android smartphone into a portable surveillance system for real-time monitoring and snapshot.

Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Shockproof for rolling stock application
- Weatherproof IP66-rated housing
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Compression: H.264/MJPEG
- Supports 4 video streams simultaneously
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Features 3DNR (3-Dimension Noise Reduction) to produce extremely clear picture quality even under low light condition
- Built-in Micro SD/SDHC card slot for local storage
- Power support: PoE (IEEE 802.3af)
- Free 64-channel monitoring software included (supports iCamSecure App)

Works Well With



POI-2002
PoE Injector




POR-1100
Outdoor PoE Repeater

Technical Specification

Camera
Image Sensor 2-Megapixel 1/2.7" Progressive Scan CMOS
Effective Pixels 1920x1080
Lens Board lens, fixed-focal, f=4.0 mm, F1.5
Angle of View (H) 78°
Minimum Illumination Color: 0.2 lux at F1.5 B/W: 0.02 lux at F1.5
Shutter Time 1 to 1/10000 sec.
Pan/Tilt/Zoom 8x digital zoom
Video
Video Compression H.264/MJPEG
Resolutions Full HD 1080p/SXGA/HD 720p/XGA/SVGA/D1/VGA/CIF
Frame Rate Up to 15 fps at 1920x1080 Up to 30 fps at 1280x1024
Video Streaming Multiple simultaneous streams, up to 4 streams
Image Setting Adjustable image size, quality and bit rate Configurable brightness, sharpness, contrast, saturation, white balance and exposure AGC/AWB/AES Back Light Compensation (BLC) Wide Dynamic Range (WDR) 3D Noise Reduction (3DNR) Flip & Mirror Portrait Mode Privacy Mask Time Stamp and Text Caption Overlay
Network
Networking 10/100 Mbps Ethernet, RJ-45
Security Multi-level user access with password protection IP address filtering HTTPS encrypted data transmission IEEE 802.1X network access control
Supported protocols IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Number of clients 20


Alarm and Event Management
Motion Detection 10 Detection Areas
Other Events Tampering Detection
Network Failure Detection Notification HTTP, FTP, SMTP
General
Local storage MicroSD/SDHC card slot
Power 802.3af PoE
Power Consumption max. 3.5W
Connectors RJ-45 10BASE-T/100BASE-TX
Button Reset Button
Operating Temperature -10°C ~ 50°C
Operating Humidity 10% to 90%, non-condensing
Housing Weather-proof IP66 rated housing
Dimensions ø117 x 50 mm
Weight 180 g
Approvals CE, FCC
Viewing System Requirements OS: Microsoft Windows 7/Vista/XP Browser: Internet Explorer 6.x or above, Firefox, Chrome, Safari Cell phone: 3GPP player Real Player: 10.5 or above Quick Time 6.5 or above
Bundled Software Bundled with 64-Channel LevelOne IP CamSecure surveillance management software

Front & Rear View



1. Lens
2. Micro SD slot
3. RJ-45 Dongle
4. Ceiling Mount

Product Diagram



Order Information

Package Content

FCS-3071: 2-Megapixel PoE Dome Network Camera

FCS-3071

Allen Wrench

Quick Installation Guide

CD Manual / Utility

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright Digital Data Communications GmbH. All Rights Reserved.