



Day/Night 1.3-Megapixel P/T PoE Network Camera



FCS-6010

H/W Version: 1

Product Overview

The LevelOne FCS-6010 with built-in high performance H.264 1.3-Megapixel CMOS sensor delivers high quality images up to 1280x1024 resolution. It is able to broadcast live images to your mobile phone or PDA, and supports 3GPP/ ISMA RSTP format for 3G mobile phones.

Build-in IR LED and ICR for Day/Night

The FCS-6010 features 10 IR illuminators built around the lens for a clear view at night up to 10 meters distance. With the built-in ICR, the FCS-6010 provides a good video quality in both day and night.

Support remote 16CH Live View


The FCS-6010 allow you to monitor up to 16 cameras video simultaneously via a Internet Explorer (ActiveX)

1.3-Megapixel with H.264 / MPEG4 / MJPEG compression

The Level1 FCS-6010 supports triple-mode video compression. In order to achieve the highest video quality and/or faster video transmission, users can select MJPEG, MPEG4 or H.264 compression mode depending on their network settings. In addition, the FCS-6010 provides many advanced features, including PoE, DI/DO, TV out (video), 2-Way audio, Micro-SD/SDHC card slot for local storage and a USB port for an upgrade to wireless connections by optional with WUA-0606 (150Mbps Wireless USB Adapter).

Bundled LevelOne IP CamSecure up to 64 channels

The FCS-6010 is bundled with the LevelOne IP CamSecure Surveillance Software. It allows users to monitor up to 64 channels simultaneously.



- | | |
|----------------------|-----------------------|
| 1. MIC | 8. Micro SD/SDHC Slot |
| 2. Status LEDs | 9. Reset Button |
| 3. Auto Light Sensor | 10. Ethernet |
| 4. IR LEDs | 11. DI/DO |
| 5. DC Jack | 12. Audio In |
| 6. TV Out (Video) | 13. Audio Out |
| 7. USB Port | |

Key Features

- 1/2.5" progressive CMOS 1.3-megapixel, 1280x1024
- Supports H.264, MPEG4 and MJPEG compression
- Frame rates: up to 1280x1024 @ 30 fps
- Support 16-CH remote view by web interface
- Removable IR-cut filter for day/night viewing
- Built-in infrared LEDs for night viewing up to 10m
- Pan/Tilt with 10x digital zoom
- Two way audio with built-in MIC
- Dual power support: DC12V / 802.3af PoE
- 1 DI/1 DO for external alarm and sensor device
- Built-in Micro-SD/SDHC card slot for local storage
- Built-in USB port for optional USB 11n Wi-Fi dongle
- Free 64-CH monitoring software (supports iCamSecure Apple App and iOS Safari)
- Remote access with Level1DNS™ service

Related Products



WCS-0030
Wireless Megapixel PIR Lighting Network Camera



FCS-1121
Megapixel PoE Network Camera

Technical Specification

Camera

Image Sensor

Sensor Type: 1/2.5" Color CMOS Sensor
 Sensor Resolution: 1280x1024 Pixel
 Minimum Illumination: 0.5 Lux@ F1.5 (IR-Off) ;
 0 Lux@ F1.5 (IR-On)

Lens

Lens Type: Board Lens
 Focal Length: f = 4mm
 View Angle: H: 76.7°, V: 58.8°, D: 94.7°
 IR, Megapixel

Infrared LEDs

10pcs of IR LEDs
 IR Illuminators up to 10 Meters
 Removable IR Cut Filter

Day and night

Automatic Removable Infrared-Cut Filter

Video & Audio

Video compression

Image Compression: H.264 / MPEG4 / MJPEG
 Auto Exposure Control / Auto White Balance /
 Auto Gain Control

Image Resolution and Frame Rate:

1280 x 1024: 30fps
 640 x 512: 30fps
 320 x 256: 30fps

Video Record

Store to PC: .asf
 Store to SD card: .mp4

Audio

Audio Streaming: Two-Way Audio
 Built-in MIC
 Audio Input / Output
 Codec : G.711/ AMR

Pan/Tilt/Zoom

Pan Range: 355°(-177.5°~177.5°)
 Tilt Range: 135°(-45°~ 90°)
 Preset: 16 Presets
 Patrol: 4 Sets
 Digital Zoom: 10x

Network

Ethernet

10BASE-T / 100BASE-TX (RJ-45)

Protocols

TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP,
 Samba, PPPoE, UPnP, RTP, RTSP, RTCP

Number of client

10

General

Power

DC 12V / 1.5A (Power Supply)
 PoE: 802.3af Compliant

Power consumption

Max Power Consumption: 12W

LEDs

Power/ Ethernet/Internet/Upgrade or Reset/Privacy

Interface & Button

DC Power Connector
 Ethernet Cable Connector
 General I/O Terminal Block
 External Audio In / Out
 TV Out (Video)
 USB Port for Optional Wifi Dongle
 Micro SD/SDHC Slot
 Reset Button

Environment

Operating Temperature: 0°C ~ 50°C (32°F ~ 122°F)
 Operating Humidity: 20% ~ 85% Non-Condensing

Dimension

108mm x 112mm x 108mm

Weight

410g

Certification

FCC,CE

Bundle Software

Bundled With 64-Channel LevelOne IP CamSecure Surveillance
 Management Software

Viewing System Requirements

Operating system

Microsoft Windows 2000, XP, Vista, 7

Web browser

Mozilla Firefox, Safari, Internet Explorer 6.x or above


Cell phone viewer

3GPP player

Stream player

Real Player 10.5 or Above
 Quick Time 6.5 or Above

Product Diagram



Order Information

FCS-6010: Day/Night 1.3-Megapixel P/T PoE Network Camera

Package Contents

FCS-6010
Power Adapter
Bracket
TV out BNC Cable
RJ45 Ethernet LAN Cable
Quick Installation Guide
CD Manual / Utility
Lens Hook

Optional accessory



WUA-0606 H/W 2.0
150Mbps Wireless USB Adapter