

LevelOne Print Server



TECHNICAL DATA

Standard Conformance:

- Ethernet II, IEEE 802.3, IEEE 802.2 SNAP

Physical Port

- LAN Port: 10/100 Base T (STP)
- Printer Port: 1 x Centronics DB-25 (FPS-2111TXU)
3 x Centronics DB-25 (FPS-2013TXU)
1 x USB1.1 (FPS-2101USB)

Protocol:

- IPX/SPX (only FPS-2111TXU and FPS-2013TXU)
- TCP/IP
- PTP over TCP/IP, PTP over NetBEUI
- Apple EtherTalk, SMB over NetBEUI

Network Environment

- Windows 95/98/NT/2000/XP
- MAC
- Unix
- NetWare NDS & Bindery

Physical Characteristics:

- Dimension: 124mm (W) x 94mm (D) x 33mm (H)
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to 70°C
- Shipping Temperature: -40°C to 70°C
- Operating Humidity: 10 ~ 80%
- Storage Humidity: 5 ~ 80%
- Shipping Humidity: 5 ~ 100%
- LEDs: Status, Error

Certification:

- FCC Part 15
- CE

Printing

- Throughput up to 200K/s
- Logical Printer: 3
- Memory: 256Kb

Special Features

- Internet Printing (proprietary)
- IPP (Internet Printing Protocol)
- Bidirectional IEEE 1284

Management:

- WebAdmin Management
- BiAdmin Management
- NWAdmin Management
- HP's JetAdmin
- SNMP Management

Power Requirement

- 12V DC External
- 5W max. (FPS-2111TXU)
- 5W max. (FPS-2013TXU)
- 3W max. (FPS-2101USB)

Ordering Information:

- FPS-2111TXU 1 Port 10/100Mbps Printer Server
- FPS-2013TXU 3 Port 10/100Mbps Printer Server
- FPS-2101USB 1 USB Port 10/100Mbps Printer Server