

Datasheet_FPS-3002USB

LevelOne's USB-Port Pocket Printer Server

LevelOne's is a compact Ethernet print server with a high-speed USB port and a single RJ-45 port. The FPS-3002USB supports multiple network protocol such as TCP/IP, PTP over TCP/IP, Apple EtherTalk, and SMB over NetBEUI to provide the cross-platform accessibility. Through the ethernet network, user can easily to finish their printing job cross LAN environment even internet. With the complete software tools, user can not only easily configure the printer remotely but also quickly setup and installation. For the features equipped, FPS-3002USB is the most demanded printer server for any environment from SOHO office to Enterprise required network printing solution.



Key Features

- Support many network protocol: IPX/SPX, TCP/IP, PTP over TCP/IP, PTP over TCP/IP, Apple EtherTalk, SMB over NetBEUI
- Embedded 1M Flash ROM, 4M RAM
- Support up to 3 Logical Printers
- Compact size for limited space
- Printing Throughput up to 650 Kbytes/sec
- Support Internet, IPP Printing
- Web Admin management
- Support Windows 95/98/ME/2000/NT, MAC, UNIX

Technical Specification

- **Printer Port**
USB Ports
- **Protocol Support**
TCP/IP
PTP over TCP/IP
PTP over NetBEUI
Apple EtherTalk
SMB over NetBEUI
- **Network Environment**
Win95/98/ME/2000/XP
MAC
UNIX
- **Network Interface**
10/100 BaseT
- **Frame Type:**
Ethernet II, IEEE802.3, IEEE802.2, SNAP
- **Memory**
Flash ROM: 1Mbytes
RAM: 4Mbytes
- **LEDs**
System Power/ Link
Status/ Error indicator
- **Power consumption**
5.5 Watts (maximum)
- **External Power Adapter**
9V DC
- **Operation Temperature**
0°C~40°C
- **Storage Temperature**
-10°C~70°C
- **Operating Humidity**
10% ~ 80%
- **Storage Humidity**
5% ~ 90%
- **Dimensions**
230mm*131.5mm*25.2mm
- **Certification**
FCC Class B

Ordering Information

- FPS-3002USB USB-Port Pocket Printer Server