




5-Port Fast Ethernet Switch



FSW-0511

H/W Version: 2

Product Overview

The LevelOne FSW-0511 is a 10/100Mbps NWay Unmanaged Switch with outstanding performance and high efficiency. With 5 NWay auto-negotiation ports, this switch fulfills the needs of connecting users on a network with automatic selection of best network speed and duplex mode.

Power Saving Features


The FSW-0511 supports Green Ethernet to provide power-saving benefits without compromising performance. One of the ways it does this is by automatically detecting the length of connected cables and can adjust power usage by saving energy on shorter cable connections.

Compact and Stylish Design

The stylish, compact wall-mountable housing of FSW-0511 fits any working environment. It comes with 5 10/100Mbps ports to meet SOHO and home network expansion needs.

Easy to Use

The FSW-0511 is plug-and-play and supports all kinds of network protocol compatibility to make installation and network management easy and fast. LED indicators provide quick, easy to read port and switch information.



1. LED Indicators
2. 10/100Mbps RJ-45 Ports
3. External Power Socket
4. Wall-Mountable

Key Features

- 5 x 10/100Mbps Auto-negotiation Fast Ethernet ports
- Auto MDI/MDI-X for each port
- Supports full duplex transfer mode for 100Mbps
- Wire speed reception and transmission
- Store-and-Forward switching method
- Supports 1K MAC addresses
- Supports 128KB RAM for data buffering
- Extensive front-panel diagnostic LEDs
- IEEE 802.3x flow control for full-duplex
- Back pressure flow control for half-duplex
- Supports LevelOne Green Technology

Works well with



GNS-1001
1-Bay Gigabit Network Storage



WBR-6603
150Mbps Wireless ADSL2+ Modem Router

Technical Specifications

Standards Compliance

IEEE 802.3 10BASE-T
IEEE 802.3u 100BASE-TX
IEEE 802.3x Flow control

Ports

5 10/100Mbps Auto MDI/MDIX Port with RJ-45 Connector

Network Media

Ethernet: 2-pair UTP Cat.3, 4, 5 up to 100M
Fast Ethernet: 2-pair UTP Cat.5 up to 100M

Protocol

CSMA/CD

Network Data Transfer Rate

Ethernet: 10Mbps (Half-duplex)
20Mbps (Full-duplex)
Fast Ethernet: 100Mbps (Half-duplex)
200Mbps (Full-duplex)

Data RAM Buffer

128KB

MAC Address Table

1K entries per device

Diagnostic LEDs

Per Unit: Power
Per Port: Link/ACT

Power Adapter

DC 9/0.6A

Power Consumption

1.93 Watts. (max.)

Temperature

Operation: -0~40°C

Storage: -40~70°C

Humidity

Operation: 10%~90 % (non-condensing)

Storage: 5%~90 % (non-condensing)


Dimensions (L x W x H)

141mm x 85mm x 27.5mm

Certification

FCC, CE

Product Diagram



Order Information

Package Contents

FSW-0511: 5-Port Fast Ethernet Switch

FSW-0511
Power Adapter
Quick Installation Guide
Wall-Mount Kit