



one world_one brand_one level_

LevelOne ProCon Fast Ethernet Fiber Switches



LevelOne 19" ProCon 8 Port 100 Mbps
Fast Ethernet Fiber (ST) or (SC) Switch

T E C H N I C A L D A T A

Product Specifications:

- Standard Compliance: IEEE802.3u and 802.3x 100Base-FX
- Transmission Mode: Full or half duplex
- Transmission Speed: 100Mbps
- MAC Address: 12KB
- Packet forwarding/filtering Rate: 148,000 packets/secs. full wire rate on 100Mbps
- Buffer Memory: 1024KB for 8 ports
- Flow-Control: IEEE802.3x for full-Duplex, back-Pressure for half duplex

Network Interface:

- 8ST.M Eight ST multi-mode fiber ports
- 8SC.M Eight SC multi-mode fiber ports
- 8SC.S Eight SC single-mode fiber ports

Cable and maximum Length

- FX(Fiber) 50,125, 62.5/125 or 100/140 m multi-mode, up to 2Km
- FX(Fiber) 8.3/125, 8.7/125, 9/125 oder 10/125 m single-mode, up to 15Km
- Selectable Duplex Mode Switch: Per fiber port FDX/HDX DIP switch

Diagnostic LEDs:

- System LED: Power
- Port LED: Linkx/Act, 100Mbps, FDX/Col

Power Requirement:

- Input Power: 100/240V AC, 50/60Hz
- Power Consumption: 43W max.

Physical Characteristics:

- Ambient Temperature: 0°C to 50°C
- Humidity: 5% to 90%
- Dimensions: 44(H) x 440(W) x 200(D) mm

Certification:

- FCC Part 15 Class A
- CE Mark Approval

Ordering Information:

- FSW-0800FXC 8 Port 100Mbps SC Fiber Switch
- FSW-0800FXT 8 Port 100Mbps ST Fiber Switch