

8-port Combo KVM SWITCH w/ Remote Console Port

The LevelOne KVM-0830 8-port combo KVM switch enables users to control and manage a server farm or computers connected to the KVM switch with either the local console or remote console port.

The KVM-0830 is a basic KVM model designed to ease the management of servers or systems connected to it. This KVM switch saves time, money, and resources by the flexibility of its usage.

Local Console

This KVM switch is easy to connect to a PS/2 or USB enabled keyboard and mouse with a VGA monitor through the local console port. This enables user to control systems connected to the KVM switch directly.

Remote Console

In order to make use of the remote control feature, a Cat.5 remote console port is included in the KVM switch. In order for the Cat.5 signal to be transmitted, a Cat.5 Receiver is needed on the remote controlling console. The KVM-9007 Cat.5 receiver converts the Cat.5 signal into a computer signal to give users the ability to control the servers and PCs from a remote location to up to 300 meters.

Large System Management

By making use of a Daisy chain, up to 120 computers can be connected to the KVM switch by cascading 8 KVM-0830/0831/0841/1630/1631/1641 together. This gives network administrator the ability to control larger groups of servers or systems from one console without the need to switching between different console stations.

The friendly user interface makes management of the KVM switch and systems connected to it easy. It also has security measures in place to protect systems from unauthorized access.



KVM-0830

Related Products



KVM-1630
16-port Combo KVM
Switch



KVM-9007
Cat.5 Receiver

Key Features

- Control servers and computers either locally via control port or remotely via Cat.5 console
- Combo architecture with PC support for PS/2 and USB interface
- Built-in Cat.5 remote console port for server access to 300 meters
- Flexible auto-scan mode for flexible PC monitoring
- Select PC's by using Hot-Keys or by switch select button
- Built-in daisy chain port for cascading with KVM-0830 or KVM-1630 up to 8 units
- Provide ACL (Access Control List) security function - store up to 8 independent ACLs for controllable PCs
- High video display quality – up to 1920x1440
- Support Windows, NetWare, Unix, Linux, Mac OS and Sun Microsystems
- 19" rackmount 1U size design

Technical Specification

Switch Ports

- **PC Port**
8-port HDB15 for PS2/USB
- **Console Port**
1 Console port for USB
1 Cat.5 Remote Console
- **Keyboard and Mouse Emulation**
PS/2 or USB
- **VGA Resolution**
1920X1440 (Local Console)

Daisy Chaining

- **Daisy Chaining**
 - Support Daisy Chaining up to 8 units
 - Connector: DB15 (Female Type)
- **Daisy Chain Max. Level**
8 units
- **Max. PC Connection**
120 PCs/Servers (cascading 1 KVM-0830 + 7 KVM-1630/1631/1641)
- **Scan Intervals**
5 ~ 99 Sec.


Switch Management

- **PC selection**
On Screen Display (OSD) Menu, Hot Key, Push Button
- **Security**
Provide ACL (Access Control List) security function, store up to 8 independent controllable PC lists
- **Hotkey**
Provide various Hotkey (Scroll-Lock/ Cap-Lock/ Num-Lock/ Alt/ Ctrl/ Win)
- **Multilingual OSD (On Screen Display) control**
8 languages (English, France, German, Spanish, Italian, Russian, Japanese, Simplified Chinese)

Physical Specifications

- **LEDs**
 - Power/Bank 3 digits display
 - Online (Blue)
- **Housing**
Metal
- **Power Adapter**
DC 12V, 1 A
- **Operation Temperature**
0 ~ 50°C
- **Storage Temperature**
-20 ~ 60°C
- **Humidity**
0~95%, Non-Condensing
- **Dimension and Size**
19" Rackmount, 1U
445 x 160 x 45
2.0 kg

Product Diagram



Order Information

KVM-0830: 8-Port Combo KVM Switch

ACC-2101: 1-to-3 1.8m cable for PS/2 and USB port

ACC-2102: 1-to-3 3.0m cable for PS/2 and USB port

ACC-2103: 1-to-3 5.0m cable for PS/2 and USB port

ACC-2109: 90cm Daisy-Chain Cable