

Datasheet_POH-0850TX

19" 8-port Mid-Span PoE Hub

LevelOne's 19" Mid-Span PoE hub is equipped with 8 RJ-45 ports featuring PoE function to eliminate the bulky power cable need while implementing your network infrastructure thus allowing greater flexibility in the locating of network devices and significantly decreasing installation costs.

The product is fully compliant with the IEEE 802.3af standard and acts as a patch panel between a switch and other network devices to provide power and data on the existing standard Cat 5 Ethernet cable. There is no need to replace your original Ethernet equipment to realize the advantage of PoE. The remote power feeding can up to 100 meters. Your network devices can be installed in more appropriate position for better performance. The embedded software utility provides GUI interface allowing you easily to configure and manage this device including auto detecting PD and power consumption, resetting the appliance remotely and providing the power central management (e.g. UPS backup system).

The compact 19", 1U rack-mountable design enables the switch to be easily located in a server room or computer lab in order to centralize power management and simplify network integration for various applications. For all the functions featured in POH-0850TX, people can get the benefits of flexible network solutions that can simplify the installation of wireless AP, network camera systems and other devices or applications in the network.



POH-0850TX

Key Features

- 8 ports power over Ethernet Hub
- IEEE 802.3af compliance
- Auto detect PD and power consumption
- Support power management function
- Per power port control/ status/ parametric information manage
- Remote power feeding up to 100 meters
- Centralized power distribution for POE powered Device (PD)
- High safety short circuit protection
- Power management information auto recover
- 19" Rack mountable size

Datasheet_POH-0850TX

Technical Specification

- **Standard Conformance**
IEEE 802.3af Power over Ethernet
- **Data in Connector**
8 x RJ-45,
Data pin : 1,2,3,6
- **Data and power out Connector**
8 x RJ-45.
Data pin:1,2,3,6,
Power pin(V+): 4,5
Power pin(V-): 7,8
- **Power management function**
Per port power feeding control
Power device detection
Power device classification control
Power sampling control
Power device discovery
PD discovery Resistor adjustable
Auto detect port status
- **LEDs**
System Power
Per port: power good, power fail
- **Power**
AC 100~240V, 50/60 Hz, 130 Watts,
IEC power socket with fuse and power switch
- **Power consumption**
100 Watts (maximum)
- **Cooling**
2 x DC fans
- **Operation Temperature**
0 ~40
- **Humidity**
90%, (non-condensing)
- **Dimensions**
440mm(L)*224mm(W)*44mm(H)
- **Certification**
FCC Class A, CE

Product Diagram



Order Information

- POH-0850TX: 8-port MidSpan PoE Hub