



POW-2440

120W 24VDC Industrial Power Supply, DIN-rail -10 to 60C


The POW-2440 is a DIN-rail industrial power supply is ruggedized, universal input voltage range and full compliance with all important safety and EMC standards. It can be operated at full load across an ambient temperature range of -10 to 60 Celsius degree without need of additional cooling to guarantee quality for harsh industrial environment.

Features

- Universal AC Input at Full Range
- Short Circuit, Overload / Over Voltage Protection
- Fanless Design
- DIN rail installation
- UL508 Approval
- Isolation Class II
- Fix Switching Frequency at 55KHz
- 100% Full Load Burn-in Test

Diagrams

Unit: mm



Specifications

Output DC	24V	Dimension & Weight	65.5 x 125.2 x 100mm @ 0.79kg
Output Current	5.0A	Operation Temperature	-10 to 60 Celsius
Output Power	120W	Operation Humidity	20 to 90% RH Non-condensing
Input Voltage	88-132VAC or 176-264VAC by switch, 248-370VDC	Safety Approval	IEC60068, EN60950-1, UL60950-1, EN55011, EN55022 (CISPR22) Class B, EN61000-3-2, EN61000-3-3, EN61000-4-2/3/4/5/6/8/11, EN61000-6-2, EN61204, EN55024
MTBF	15.6 years		

Order Information

POW-2440 - 120W 24VDC Industrial Power Supply, DIN-rail -10 to 60C

Package Contents

POW-2440