# Datasheet WPS-0104

### 11g Wireless USB-Port Printer Server

LevelOne's WPS-0104 is a high-performance wireless print server that provides a simple and efficient network printing solution. It is designed to act as a wireless station with high-speed IEEE 802.11g wirelss networks, delivering data transfer rate up to 54 Mbps. The equipped USB 2.0 pritner port performs a high-bandwidth data transfer. The compact size design allows the Wireless Print Server to be used even where space is limited. Network security is protected by 64/128 bit WEP encryption. The IPP printing method allows remote printing from a PC to any accessible printer. Besides, for the seamless connection between heterogeneous working environment, WPS-0104 supports all major operating systems including Windows 95/98/ME/2000/XP, Macintosh OS 9.x, 10.x and Unix.



**WPS-0104** 

## **Key Features**

- Compliant with IEEE 802.11g and 802.11b standards
- High performance USB 2.0 printer port
- Web-based Management
- Embedded 1M Flash ROM, 4M RAM
- Compact size for limited space

- Printing Throughput up to 650 Kbytes/sec
- Supports Internet, IPP Printing
- Supports Windows 95/98/ME/2000/XP, Macintosh and Unix
- Supports IPX/SPX, TCP/IP, PTP over TCP/IP, PTP over TCP/IP, Apple EtherTalk, SMB over NetBEUI

# Datasheet\_WPS-0104

### **Technical Specification**

Protocol Compliance

Wireless: IEEE 802.11b; IEEE 802.11g Ethernet: IEEE 802.3; IEEE 802.3u

Ports

Printer Port: 1 x USB Ethernet: 1x RJ45

Antenna:

2dBi gain Antenna

Range Cover:

IEEE 802.11b: indoor: 50m, outdoor: 150m IEEE 802.11g: indoor: 30m, outdoor: 60m

Printing Methods:

PTP over TCP/IP or NetBEUI protocol, LPD printing

SMB over TCP/IP or NetBEUI printing IPP (Internet Printing Protocol)

AppleTalk

OS Support:

Windows 95/98/ME/ 2000/ XP, Macintosh 9.x, 10.x, Unix

Management Tools

BiAdmin, Web-based management, Set-up Wizard

Security Support:

64/128 bit WEP, ESSID

■ Temperature:

Operating:  $0^{\circ}$ C ~40°C Storage: -10°C ~70°C

Humidity:

Operating: 10% ~ 80% Storage: 5% ~ 90% ■ Power Supply:

DC 5V / 2A

DC 3V / Z/

LEDs:

Power status \*1 WAN \*1/ LAN \*1

USB \*1

Dimension:

95.5mm(L) \* 65mm(W) \* 27mm(H)

EMI and Safety:

CE

#### **Product Diagram**



**WCS-0104 Diagram (Infrastructure mode)** 



PC with Wireless Network Adapter

WCS-0104 Diagram (Ad-Hoc Mode)

#### **Ordering Information**

WCS-0104:11g Wireless USB-Port Printer Server

