Datasheet_FBR-1417TX

1W, 4L VPN Router w/1 Parallel+ 1 USB Printer Server

LevelOne's FBR-1417TX is a high-performance and fully featured Ethernet VPN Router with an integrated 4-port switch. Up to 4 workstations can be connected to this router by 4 Ethernet ports that support 10/100 Mbps data transfer rate and auto MDI/MDIX function. With one parallel port and one USB printer port, FBR-1417TX connects to the most available printer and performs highbandwidth data transfers. The included printer server application supports multiple operating systems for seamless connection with different working environments.

The VPN features are supported securely to protect data transfer among different groups and to prevent unexpected access by hackers. With its advanced security functions, FBR-1417TX supports NAT firewall with SPI mode to protect the network against DoS attacks and to prevent unwanted access by potential hackers.

To keep up with changing technologies, we can easily upgrade firmware by web based interface or windows utilities. There is no need to worry about complex network configuration, this friendly setup environment allows users manually to configure the advanced settings that include LAN, WAN setting, access restrictions and creating system status logs through the general web browser.



FBR-1417TX

Key Features

- Integrates with 4 ports Fast Ethernet switch: 10/100Mbps MDI/MDIX auto-sensing.
- Provides 10/100Mps WAN interface to connect with DSL or cable modem for broadband Internet access.
- Built-in one parallel port and one USB port for printer connection
- Browser-based interface configuration and management: OS independent, easy-to-use for consumer install.

- Supports VPN server of IPSec, L2TP and PPTP
- Built-in NAT function: allow multiple PCs and devices to share one Internet connection.
- Printer server supports Windows 98SE/ME/2000/XP, Macintosh and Unix operation system
- Easy to upgrade: using Web or windows utility to upgrade firmware

Technical Specification

- Protocol Compliance Ethernet: IEEE 802.3; IEEE 802.3u
- Ports

LAN: 4 x RJ45, 10/100Mbps with Auto-MDI/MDIX WAN: 1 x RJ45, 10/100Mbps with Auto-MDI/MDIX Print Port: 1 x USB (v1.1); 1 x Parallel (DB25,F)

- Memory Flash: 1MB DRAM: 8MB
- WAN Type Static IP Address Dynamic IP Address (DHCP Client) PPPoE PPTP L2TP
- NAT Functions
 Virtual Server
 Special Application
- DMZ Host
 VPN Features
 VPN server of IPSec, L2TP and PPTP
 IPSec, L2TP, PPTP Pass Through

- Access Control MAC / IP Filter Domain Access Control
- Firewall NAT Firewall with SPI mode DoS Detection
- Other Features Supports DDNS, UPnP, SNMP
- Print Server OS Support: Windows 98SE/ME/2000/XP, Unix LPR, Mac OS
- Temperature Operating: 0°C ~40°C; Storage: -20°C ~70°C;
- Humidity Operating: 10%~90% non-condensing; Storage: 0%~95% non-condensing
- Power Supply DC 5V/2A
- EMI and Safety FCC, CE





Ordering Information

• FBR-1417TX : 1W, 4L VPN Router w/1 Parallel+1 USB Printer Server

Logistic Information

Package Information	Package N.W	Package G.W	CUFT/CTN
10 Pc/CTN	12 Kg	13 Kg	2.25

le	V	eľ
0	n	е