

# **P/T IP Network Camera**

# H/W Version: 1

### **Product Overview**

The FCS-0020 Network Camera is a user-friendly and motorized Pan/Tilt network camera. Whether for Home, or Business surveillance, or for entertainment and fun, this network camera provides all the features needed for an affordable and easy to use IP Surveillance camera.

### Motorized Pan/Tilt with Multiple Video and Bidirectional Audio

The FCS-0020 features a Micro Stepping Motor for precision pan and tilt control from a local console or remotely via the Internet. With enhanced MPEG-4 and Motion-JPEG Video compression, users can enjoy high quality imagery that requires minimum bandwidth. The camera also supports bi-directional audio communication.

FCS-0020

### **Motion Detection & E-mail Alerts**

Users can define 4 motion-detection regions, each with adjustable size and sensitivity. When motion is detected the system sends an automated E-mail alert or sends captured images via FTP upload to a designated storage server.

# Bundled LevelOne IP CamSecure Lite and Windows

The FCS-0020 Pan/Tilt Network Camera is bundled with LevelOne IP CamSecure Lite. It is an easy to use surveillance management tool that allows users to monitor the camera locally over the LAN or remotely over the Internet.





1. Built-in Microphone

- 2. Power
- 3. Speaker
- 4. Microphone In
- 5. Network
- 6. Reset

### **Key Features**

- Triple Streaming for MPEG4, Motion-JPEG and Mobile device simultaneously
- Features a built-in microphone and external audio in/out jacks
- Supports up to 25/30 frames per second in full VGA resolution
- Features Motion Detection and Event-notification via E-mail
- Supports a variety of browsers for live viewing: IE, Firefox, Safari, Mozilla, Netscape
- Remote viewing over the Internet or via 3G Mobile phone
- Bundled with LevelOne IP CamSecure Lite 32-CH surveillance management software

### Works Well With



FCS-9464 IP CamSecure Pro64 Mega




**FCS-7011** 1-port PoE Video Server

# **Technical Specification**

Tilt
64°
Digital Zoom
4x Digital Zoom
Hardware & Environment
Flash ROM
4MB Flash ROM
SDRAM
32MB SDRAM
Housing
Indoor
Power
DC5V/2A
Environmental Conditions
Operating Temperature: 0°C ~ 40°C
Operating Humidity: 10% ~ 80%
Storage Temperature: 0°C ~ 40°C
Storage Humidity: 10% ~ 80%
Dimension
113.5mm (H) x 52.1mm (W) x 80mm (D)
Weight
263g without stand
367.5g with stand
Supported Protocols
IPv4, TCP/IP, SMTP, HTTP, DHCP, NTP, RTSP/RTP, UPnP
Software
Bundled with 32-Channel LevelOne IP CamSecure Lite
surveillance management software
Viewing System Requirement
OS
Microsoft Windows 2000/XP/Vista
Browser
For MPEG4 video: Internet Explorer in Windows
For MJPEG video: Internet Explorer in MAC, Firefox, Safari,
Mozilla, Netscape
3GPP Player
Real Player 10.5 or above
Quick Time 6.5 or above
EMI and Safety
FCC, CE

# **Product Diagram**



Order Information Package Contents

# FCS-0020: P/T IP Network Camera

FCS-0020 Power Adapter Camera Stand CD Manual/Utility Quick Installation Guide

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

 $\ensuremath{\mathbb O}$  Copyright 2008 Digital Data Communications GmbH. All Rights Reserved.