

# P/T/Z Network Camera

# The second secon

FCS-1040

H/W Version: 2

LevelOne's FCS-1040 is a state-of-the-art Internet camera that features motorized Pan Tilt Zoom functions and a built-in web server to deliver high quality live video through existing Ethernet connections.

# **High-Quality Video and Two-way Audio**

The FCS-1040 contains an excellent CCD sensor that records ideal images up to 704 x 480 pixels. This device employs not only Motion-JPEG compression to transfer superior video streaming but also combines high quality images with sound provided by a built-in microphone to generate streaming video in MPEG-4 (Simple Profile) format. Two-way audio provides voice communications during an alarm event.

#### Pan/Tilt/Zoom

The FCS-1040 provides advanced camera features combining a 10x optical zoom lens with

up to 10x digital zooming that allows for 100x zooming capability. The Auto Pan function allows the user to define automatic panning movements of individual cameras thus providing the capability to survey the widest range of targets: A pan range of 270-degrees and a tilt range or 90-degrees. The Patrol mode allows the user to preset up to 20 spots for sequential auto-monitoring.

#### **Ideal for Surveillance Solutions**

With LevelOne's free bundled software, administrators are able to monitor up to 32 channels simultaneously. The FCS-1040 also provides recording capabilities for synchronized video & audio when captured by manual, event-driven or schedule recording modes. For full-featured surveillance solutions to your camera needs, the LevelOne's FCS-1040 absolutely provides optimum solutions when building a digital surveillance environment.





- 1. Status LED
- 2. Built-in Microphone
- 3. Power Cord Socket
- 4. LAN Port
- 5. Audio In
- 6. Digital Input/Output
- 7. Audio Out

#### **Key Features**

- MPEG4/ MJPEG Compression Selectable
- Motorized Pan/Tilt/Zoom (10x optical zoom)
- Optimal Synchronization of Audio & Video
- Supports Auto Pan/ Auto Patrol Modes
- Intelligent Motion Detection
- Pre/Post Alarm Snapshots
- Extended I/O for Sensor & Alarm
- Free software included (Industry-leading 32-channel IP CamSecure Lite™ software)

#### **Works Well With**



FCS-9464 IP CamSecure Pro64 Mega



FCS-7011 1-Port PoE Video Server

# **Technical Specification**

#### Network

#### **Standards Compliance**

IEEE 802.3 10BaseT Ethernet

IEEE 802.3u 100Base-TX Fast Ethernet

#### **Ports**

1 x RJ-45 10/100 Mbps port

#### Video

#### **Compression Mode**

Streaming video: MPEG4 (Simple Profile)/ MJPEG

selectable Still Image: JPEG

# Max. Resolution

704x480 pixels(NTSC) 704x576 pixels(PAL)

#### **Frame Rate**

176x120: 30/25fps 352x240: 30/25fps 704x480: 15/12fps

#### **Still Picture**

JPEG

#### **Video Record**

AVI

#### Camera

#### Sensor

1/4 inch color CCD sensor

#### Lens

Focal length: 4.2~42mm Aperture: F1.8~2.9

# View Angle

Vertical 36°-3.6° Horizontal 47°- 4.9°

#### Minimum Illumination

Typical: 1.5 Lux / F1.8; Low Lux mode: 0.05 Lux/F1.8

#### **Electronic Shutter (Sec)**

1/60~1/100,000(NTSC), 1/50~1/100,000(PAL)

# AGC/AWB/AES

# **Auto Iris Control**

# Audio

#### Audio In

External Microphone Input\*1

# **Built-in Microphone**

Omni-directional

Frequency: 20 – 20,000Hz

# **Audio Out**

Audio output connetor

#### **Audio Codec**

8/24/32kbps Full-Duplex

# S/N Ratio

>58dB

#### PTZ

#### Pan

270 ° (Range+135 ° ~-135 °)

#### Tilt

135 ° (Range +90 ° ~-45 °)

#### **Number of preset positions**

20

#### **Digital Zoom**

2x,4x,6x,10x digital zoom

#### **Optical Zoom**

1x~10x optical zoom

# **Hardware & Environment**

#### Flash ROM

4MB Flash ROM

#### **SDRAM**

16MB SDRAM

# Housing

Indoor use

DOH-1000/DOH-1100 optional for IP66-rated outdoor use

#### Digital I/O

1 sensor input(max. 12VDC 50mA)

1 relay output(max. 24VDC 1A, 125VAC 0.5A)

#### **Power**

Consumption: 13 W (Max.) Adapter output: 12VDC, 1.5A

#### **Temperature**

Operating: 0-40°C/32-104°F

# Humidity

Operating: 85% (RH)

#### **Dimension**

105mm(L) \* 104mm(W) \* 125mm(H)

# Weight

420g

# Software

Bundled with 32-Channel LevelOne IP CamSecure Lite surveillance management software

# **Viewing System Requirement**

#### OS

Microsoft Windows 2000/XP/Vista


#### **Browser**

IE 6.x or above

# **EMI** and Safety

FCC, CE

# **Product Diagram**



**Order Information** 

FCS-1040: P/T/Z Network Camera

**Package Contents** 

FCS-1040

Power Adapter Camera Stand

AC Cable

CD Manual/Utility

Quick Installation Guide

# **Optional Accessories**



**DOH-1000**Domed Outdoor Housing



**DOH-1100**Heavy-Duty Domed Outdoor Housing