

# H.264 MegaPixel PoE Network Camera

### H/W Version: 1

The LevelOne FCS-1121 IP camera offers reliable and excellent video quality solution for 24-hour surveillance application. Users can view live, motion image from anywhere through web browser or mobile phone via the Internet or 3G network respectively. With the mega pixel progressive sensor and builtin removable IR-cut Filter, it delivers the extremely clear and detailed images that CCTV cameras cannot provide.

For easy setup, "Easy Installation Wizard" makes the configuration simple even for users without IT background. This LevelOne IP camera simplifies the hardware and software installation by flexible design and multiple applications. In other words, the FCS-1121 is not only for normal home security but also suitable for demand of professional surveillance such as bank, office building, and factory applications.

#### **Remote Viewing Made Easy**

Level1DNS<sup>™</sup> service, an intelligent dynamic DNS service which is handy at situation where IP address of your LevelOne device is not permanent, which is

#### **Key Features**

- Megapixel (1280 x 800) high-definition resolution
- Compression: H.264/MPEG-4/MJPEG
- Supports 2 video streams simultaneously
- Easy Internet monitoring via configuration free Level1DNS<sup>™</sup> service
- Digital input/output (1DI/1DO) for sensor and alarm
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Built-in microphone and external speaker for 2-way audio communication
- Built-in SD/SDHC card slot for local storage
- Removable IR-cut filter for day and night surveillance
- Built-in 4-pin auto iris lens connector
- Free 64-channel monitoring software included (supports iCamSecure App)



FCS-1121

frequently changed by your ISP. By offering you an unique domain name, our Level1DNS<sup>™</sup> service ensures your device is always reachable from anywhere around the globe and easy remote access through web browsers.

#### **64-channel Management Software**

We aim to offer you the most versatile and comprehensive surveillance solutions. Our IP CamSecure software coming with the camera allows you to monitor up to 64 megapixel IP cameras simultaneously on one screen to enhance scalability. For added convenience and flexibility, the software includes various advanced features such as scheduling recording, event alert, and heaps more. In addition, simply install our free iCamSecure App to your smartphone and connect to the PC with IP CamSecure software installed, you will easily turn your iPhone/ Android smartphone into a portable surveillance system for real-time monitoring and snapshot.

#### **Works Well With**



NVR-0204 4-CH Network Video Recorder



**BOH-1200** PoE Upgradable Outdoor Housing with Infrared LEDs

## **Technical Specification**


Camera	Alarm and Event Management
Image Sensor	Motion Detection
Megapixel 1/4" Progressive Scan CMOS	3 Detection Zones
Effective Pixels	Notification
1280x800	HTTP, FTP, SMTP, Samba
Lens	DI/DO
C/CS-mount, fixed-focal, f=4.2 mm, F1.4	1 D/l and 1 D/O for external sensor and alarm
Angle of View (H)	General
71°	Processor and memory
Minimum Illumination	CPU: 500 MHz
1 lux	Flash: 16M
IR Cut Filter	RAM: 64M DDR
Removable infrared-cut filter for day & night function	Local storage
Pan/Tilt/Zoom	SD/SDHC card slot
4x digital zoom	Power
Video	DC12V 1A / AC24V / 802.3af PoE
Video Compression	Power Consumption (Max.)
H.264 / MPEG4 / MJPEG	8W
Resolutions	Connectors
1280x800 / 640x400 / 320x192	RJ-45 10BASE-T/100BASE-TX
Frame Rate	Auto Iris (DC Drive)
Up to 30 fps at all resolutions	3.5mm line out
Video Streaming	
Multiple simultaneous streams, up to 2 streams	I/O terminal block (DI/DO)
Image Setting	DC power jack (12V)
- Adjustable image size, quality and bit rate	AC power terminal block (24V)
- Configurable brightness, sharpness, contrast, saturation,	LED Indicator
white balance and exposure	Power/Link
- ACG/AWB/AES	Button
- Flip & Mirror	Reset Button
- Privacy Mask	Operating Temperature (°C)
- Time Stamp and Text Caption Overlay	0°C ~ 50°C
Video Format	Operating Humidity (Non-condensing)
Store to PC: ASF	10% to 80%
Store to SD card: MP4	Dimensions
Audio	120 x 60 x 60 mm
Audio Streaming	Weight
2-way audio	380 g (without lens)
Audio Compression	Approvals
G.711 / AMR	CE, FCC
Audio Input/Output	Viewing System Requirements
Built-in microphone	OS: Microsoft Windows 7/Vista/XP
Mic/line input, line output	Browser: Internet Explorer 6.x or above
Network	Cell phone: 3GPP player
Networking	Real Player: 10.5 or above
10/100 Mbps Ethernet, RJ-45	Quick Time 6.5 or above
Security	Bundled Software
Multi-level user access with password protection	Bundled with 64-Channel LevelOne IP CamSecure surveillance
IP address filtering	management software
HTTPS encrypted data transmission	
Supported protocols	-
TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP,	
Samba, PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP Number of clients	-
10	
DNS	_

Easy Internet monitoring via configuration free Level1DNS™ service

#### **Front View and Rear View**



#### **Product Diagram**



Order Information	FCS-1121: H.264 MegaPixel PoE Network Camera
Package Contents	FCS-1121
	Power Adapter
	RJ-45 Ethernet LAN Cable
	Quick Installation Guide

CD Manual / Utility

#### **Optional Accessories**



CAS-1300 2.8-8.5mm Vari-Focal Day/Night Megapixel Lens

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright Digital Data Communications GmbH. All Rights Reserved.