

# H.264 1.3-Megapixel PoE Network Camera



FCS-1141

### H/W Version: 1

The LevelOne FCS-1141 is a 1.3 Megapixel PoE HD WDR Network CCD Camera, ideal for video surveillance systems where clear images and greater image detail are required. It is the perfect solution for securing areas where high quality identification is needed, such as airports, passport controls and casinos.

The FCS-1141 has a superior, highly sensitive Sony image sensor and has good low-light performance. It features automatic day and night functionality with removable infrared-cut filter for increased light sensitivity. In addition to MPEG-4 and MJPEG real time streaming, the HD WDR IP Camera has a superior H.264 codec to smoothly transfer High Definition surveillance data through Internet without distortion.

The built-in Wide Dynamic Range (WDR) function allows getting crystal clear images even in extreme conditions; this feature enhances the camera's performance in installations including shops, banks, parking lots, factories and building surveillance.

The integrated BNC connector allowing the FCS-1141 to be connected directly to an analog monitor, providing enhanced flexibility and usability and ease of installation. Together with PoE, activity adaptive streaming, and the included 32-CH LevelOne IP CamSecure Lite surveillance management software the FCS-1141 is indisputably the top choice for reliable and high performance surveillance.



- 1. Lens
- 2. Reset
- 3. Power LED
- 4. 4-pin Auto Iris Connector
- 5. GPIO
- 6. AC/DC power din
- 7. Micro SD/SDHC Card slot
- 8. Audio Out
- 9. Audio In
- 10. LAN Port
- 11. BNC Connector

## **Key Features**

- 1.3 Megapixel Sony Progressive Scan CCD sensor
- HD 720p Real-time at dual streaming
- H.264, MJPEG, and MPEG-4 compression
- Integrated Real-time WDR
- 2D / 3D Noise Reduction
- Motion Detection & Privacy Masks
- True Day Night with Infrared Cut Filter (ICR) IR Sensitive
- BNC connector for analog video output
- Two-way audio
- Local storage with Micro SD/SDHC slot
- \*Free 32-CH Monitoring Software Included

### **Works Well With**



**FSW-0503** 4 FE PoE + 1FE Switch



NVR-0216 16-CH Network Video Recorder

# **Technical Specification**

### Camera

**Image Sensor** 

Image Sensor: 1/3" Sony Progressive CCD Picture Elements: 1280(H) x 960 (V)

Minimum Illumination: Color 0.03 lux @ F 1.2

B/W 0.001 lux @ F 1.2

Shutter Speed: 1~ 1/10000 sec.

White Balance: Manual / ATW (1500 ~ 15000K)

Lens

Lens Type: Fixed lens (CS-mount) Focal Length: f=4mm; F/1.5 View Angle: H: 65.4°, V: 49.9°

IR, MegaPixel

# Video

### Video

Video Compression: H.264 / MJPEG / MPEG-4 Video Streaming: Simultaneously H.264+MJPEG or H.264+MPEG4

Resolution:

H.264: 1280x960/HD 720p/D1/VGA/QVGA/CIF/QCIF MJPEG: 1280x960/HD 720p/D1/VGA/QVGA/CIF/QCIF MPEG-4: 1280x960/HD 720p/D1/VGA/QVGA/CIF/QCIF

## **Image Resolution and Frame Rate:**

1280 x 960 @ 12.5/15 fps

720p @ 25/30fps

## **Image Setting**

Brightness: Manual

Exposure: Auto / Manual / Fixed Shutter

Backlight: On/Off Sharpness: Manual Contrast: Manual

White Balance: Auto / Manual/Indoor / Outdoor

Digital Zoom: 1x ~ 16x

Image Rotation: Flip, Mirror, and 180° Rotate

WDR: Off / 4 Level Adjustment 3D Noise Reduction: On/Off

Privacy Mask: On/Off

Privacy Mask Type: Transparent, Color

ICR: Auto/On/Off

Zoom

Digital Zoom: 16x

# Audio

# **Audio streaming**

Two-way

# Input/output

Line out, Line in/Mic in

# **Audio Compression:**

G.711/G.726

### Network

Interface: 10/100Mb Ethernet (RJ-45)

Protocol: TCP/IP, UDP, RTP, RTSP, HTTP, ICMP, FTP, SMTP, DHCP

and IGMP

Password Levels: User and Administrator Internet Browser: Internet Explorer (6.0+)

User Account: 20

### Mechanical

### Interface:

Power: 3 pins terminal block

Ethernet: RJ-45

Micro SD slot: Support Micro SD/SDHC (card is not included)

Audio: Stereo phone jack, Ø 3.5mm Alarm: 4 pins terminal block, pitch 3.5mm

Auto Iris: DC Drive

Analog Video: 1.0 Vp-p / 75 Ω, BNC

### LED Indicator:

Power, Link, ACT

#### Alarm

Input: 5V 10kΩ pull up

Output: Photo Relay Output 300VDC/AC

4 pins terminal block

#### General

#### Hardware

Flash ROM: 32MB SD RAM:128MB

# **Operating Temperature:**

0°C ~ 50°C

# **Operating Conditions:**

Humidity: 10% to 90%, No Condensation

#### Power:

DC12V / PoE / AC24V

# **Power Consumption:**

6W

### Certification:

CE, FCC, RoHS Compliant

# Dimension:

135 x 75.6 x 52 mm (L x W x H) (w/o lens)

### Weight:

360 g (0.80 lb)

# **Viewing System Requirements**

### Operating system

Microsoft Windows 2000, XP, Vista, 7

# Web borwser

Mozilla Firefox, Safari, Internet Explorer 6.x or above


# Cell phone viewer

3GPP player

# Stream player

Real Player 10.5 or above Ouick Time 6.5 or above

# **Product Diagram**



Order Information
Package Contents

FCS-1141: H.264 1.3-Megapixel PoE Network Camera

ge Contents FCS-1141

Power Adapter

Camera Stand

DC jack cable(black)

RJ-45 Ethernet LAN Cable

Quick Installation Guide

CD Manual / Utility