

Day/Night IP Dome Camera (Indoor/Outdoor Operation)



FCS-3000

H/W Version: 2

LevelOne's FCS-3000 is a powerful IP network camera that features IP66 rated waterproof metal housing, making it ideal for outdoor and indoor surveillance installations. It delivers outstanding color images at low or no light conditions through LAN/WAN connections.

Vandal-proof Protection

The water-resistant design of the dome allows this camera to be installed at indoor/outdoor locations. The metal housing also provides protection to withstand impact and tampering in tough operating condition.

24 Hours Surveillance Application

The FCS-3000 contains an excellent high-resolution 1/3" CCD sensor which can record color images up to 704 x 480 pixels in low or no light conditions. It has built-in IR LEDs that capture crisp monochrome images. It employs selectable MJPEG and MPEG-4 (Simple Profile)

compression to transfer high quality streaming video and sound.

Advanced Monitoring Features

The motion detection feature allows recording only when motion is detected thus saving storage. The I/O interface allows connections to optional modules, including motion sensors, alarms smoke detectors, etc, sends emails to designated addresses when an alert is triggered.

Software Induded

The bundled software that comes with the FCS-3000 allows monitoring of up to 32 channels simultaneously. Recording of video & audio can be done easily in manual, event-driven or schedule recording modes. These features make LevelOne's FCS-3000 the cost efficient device for building a 24-hour digital surveillance network for daylnight and indoor/outdoor use.





- 1. Audio In
- 2. Audio Out
- 3. BNC Connector
- 4. LAN Cable
- 5. Power Cord Socket
- 6. Alarm

Key Features

- Includes infrared LEDs for 10m effective night vision
- High-Resolution 1/3" CCD sensor
- Vandal-proof and IP66 waterproof
- Supports selectable MJPEG/ MPEG4 (Simple Profile) compression for bandwidth-efficiency
- Supports 2-way (full-duplex) audio
- Intelligent Motion Detection
- Extended I/O for event trigger sensor & alarm
- Provides BNC video output for CCTV system
- Free software included (Industry-leading 32-channel IP CamSecure Lite™ software)

Works Well With



FCS-9464 IP CamSecure Pro64 Mega



FCS-7011 1-port PoE Video Server

Technical Specification

Network

1 x RJ-45 10/100 Mbps port

Video

Compression Mode

MPEG4/MJPEG

Max. Resolution

704x480 pixels(NTSC)

704x576 pixels(PAL)

Frame Rate

Up to 30/25 frames at 176x120/176x144

Up to 30/25 frames at 352x240/352x288

Up to 15/12 frames at 704x480/704x576

Still Picture

JPEG

Video Record

AVI

Camera

Sensor

1/3" color CCD sensor

Lens

3.6mm, F2.0

View Angle

Vertical 54°

Horizontal 67°

Minimum Illumination

0 Lux when IR on;

Infrared Facility

Infrared LEDs for 10M distance

Electronic Shutter (Sec)

1/60 to 1/100,000 sec

AGC/AWB/AES/BLC

Audio

Audio In/Out

External microphone input jack

External speaker output jack

Audio Codec

8/24/32kbp Full-Duplex

S/N Ratio

>60dB

Zoom

Digital Zoom

4x

Hardware & Environment

Flash ROM

4MB Flash ROM

SDRAM

16MB SDRAM

Housing

Indoor/Outdoor use

IP66 water-proof

Vandal-proof

Day/Night

Infrared LEDs for 10M Night view

Digital I/O

1 sensor input(max. 12VDC 50mA)

1 relay output(max. 24VDC 1A, 125VAC 0.5A)

Power

12VDC,1.5A

Temperature

Operating: 0°C -50°C (32°F -122°F)

Humidity

Operating: 95% (RH)

Dimension

Ø 127mm x 113mm (H)

Weight

830g

Supported Protocols

TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS, DHCP, DDNS and UPnP

Software

Bundled with 32-Channel LevelOne IP CamSecure Lite surveillance management software

Viewing System Requirement

OS

Microsoft Windows 2000/XP/Vista


Browser

IE 6.x or above

EMI and Safety

FCC, CE

Product Diagram



Order Information
Package Content

FCS-3000: Day/Night IP Dome Camera (Indoor/Outdoor Operation)

FCS-3000

Power Adapter

Screw Pack

CD Manual/Utility

Quick Installation Guide