

2-Megapixel PoE Dome Network Camera



FCS-3071

H/W Version: 1

The LevelOne FCS-3071 is a compact, rugged H.264 2-Megapixel PoE Mini Dome Camera designed for tough environments. The casing is tamper-resistant, it can withstand vibration, humidity, dust and fluctuating temperatures found. for example buses and trains.

The FCS-3071 is a palm-sized, discreet network camera specifically designed for mass transit vehicles. The flat tamper-resistant casing makes it ideal for installation.

The IP66 rating provides a rugged package for both indoor and outdoor applications.

In compatible with EN50155, the standard for electronic equipment operating in railway vehicles, the FCS-3071 is an economical mobile surveillance solution with high reliability and rugged performance.

The FCS-3071 utilizes PoE (Power-over-Ethernet), allowing it to be operated and powered from a single Ethernet cable, giving greater ease of installation and cost savings. In order to facilitate onboard storage and data portability, the FCS-3071 is also complete with a Micro SD/SDHC card slot for local recording.



- 1. Lens
- 2. Micro SD slot
- 3. RJ-45 Dongle
- 4. Celling Mount

Key Features

- 2-Megapixel Progressive Scan CMOS Sensor
- Dual streaming simultaneously
- H.264 and MJPEG Compression
- Shockproof for Rolling Stock Applications
- Weatherproof IP66 housing & RJ-45 dongle cable
- Micro SD/SDHC Card Slot for On-Board Storage
- Powered by PoE(802.3af) Only
- *Free 32-CH Monitoring Software Included

Works Well With



NVR-0104 4-CH Network Video Recorder



FSW-0503 4 FE PoE + 1FE Switch

Technical Specification

Camera

Image Sensor

Image Sensor : 1/2.7" Progressive CMOS Picture Elements : 1920(H) x 1080(V)

Minimum Illumination: Color: 0.2 lux @ F 1.2

Shutter Speed: 1~ 1/10000 sec.

White Balance: Manual / ATW (1500 ~ 15000K)

Lens

Lens Type: Board Lens Focal Length: f=4.0mm; F/1.5 View Angle: H: 78°, V: 52° Camera Angle: 0-90°(Tilt and Pan)

Video

Video

Video Compression: H.264 / MJPEG

Video Streaming: Simultaneously H.264 + MJPEG

Resolution:

H.264 Full-HD 1080p/HD 720p MJPEG Full-HD 1080p/HD 720p/D1/CIF

Image Resolution and Frame Rate:

HDTV 1080P (1920x1080) @ 12.5/15 fps HDTV 720p (1280x720) @ 25/30 fps

Image Setting

Brightness: Manual Exposure: Auto / Manual Sharpness: Manual Contrast: Manual

White Balance: Auto / Manual

Saturation: Manual Hue: Manual

Digital Zoom: Zoom-In/Zoom-Out Motion detection: ON/OFF

Privacy Mask: ON/OFF

Privacy Mask Type: Transparent, Color

Zoom

Digital Zoom: 16x

Network

Interface: 10/100Mb Ethernet (RJ-45)

Protocol: TCP/IP, UDP, RTP, RTSP, HTTP, ICMP, FTP, SMTP, DHCP

and IGMP

Password Levels: User and Administrator Internet Browser: Internet Explorer (6.0+)

User Account: 20

Mechanical

Interface:

Ethernet: RJ-45 dongle cable with PoE

Micro SD slot: Micro SD/SDHC support (card is not included)

General

Hardware

Flash ROM: 128MB SD RAM:128MB

Casing:

IP66-rated for rain and dust protection, Plastic

Operating Temperature:

-20°C ~ 50°C

Operating Conditions:

Humidity: 10% to 90%, No Condensation

Power

802.3af compliant Power-over-Ethernet(PoE)

Power Consumption:3W

Certification:

CE, FCC, RoHS Compliant

Dimension:

110 x 50 mm (4.3 x 2.0 Inches) Ceiling Mountable

Weight:

180 g (0.40 lb)

Viewing System Requirements

Operating system

Microsoft Windows 2000, XP, Vista, 7

Web borwser

Mozilla Firefox, Safari, Internet Explorer 6.x or above


Cell phone viewer

3GPP player

Stream player

Real Player 10.5 or above Quick Time 6.5 or above

Product Diagram



Order Information

FCS-3071: 2-Megapixel PoE Dome Network Camera

Package Content

FCS-3071

Allen Wrench

Quick Installation Guide

CD Manual / Utility

Optional Accessories

