



FCS-3073 Version: 1

! Power supply unit is to be ordered separately.

GEMINI Fixed Dome IP Network Camera, 2-Megapixel, 802.3af PoE, Vandalproof, Indoor/Outdoor

The LevelOne FCS-3073 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3073 offers 2-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- Weatherproof IP66-rated housing
- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264, MJPEG
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Removable IR-cut filter for day and night surveillance
- Supports IPv4/IPv6 network operation
- Vandal-proof IK10-rated housing
-
- Built-in Micro SD/SDHC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS

Image Sensor:

2-Megapixel 1/2.8" ProgressiveScan CMOS

Lens:

Board lens, Fixed-focal, f=6.0mm, F2.0

**Port:**

1 x RJ-45 10/100 Mbps PoE port
1 x MicroSDHC card slot

Button/Knob:

Reset Button

Shutter Time:

1~ 1/10,000 sec.

Angle of View:

52°

Pan/Tilt/Zoom:

digital zoom

Video Compression:

H.264 / MJPEG

Resolution:

2M (1920x1080)

Output Video Format:

AVI

Power Input:

802.3af PoE
12VDC/1A

Power Consumption:

3.5W

Data Rate:

10/100Mbps

Storage Capacity:

SD/MicroSD memory card of up to 16GB

Features

General:

Backup: MicroSDHC card slot for local storage
IPv6: IPv4/IPv6 network operation

Security:

Alarm and Notification: Alarm: Motion Detection; Tampering Detection; Network Failure Detection
Notification: HTTP, FTP, SMTP
Access Control: Multi-level user access with password protection
IP address filtering
IEEE 802.1X network access control
HTTPS encrypted data transmission

Video:

Image Setting: - Adjustable image size, quality and bit rate
- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR)
- 3D Noise Reduction (3DNR)
- Flip & Mirror
- Portrait Mode
- Privacy Mask
- Time Stamp and Text Caption Overlay

Image Layout:

Streaming: Up to 2 video streams
Motion Detection

Performance

Number of Clients:

20

Frame Rate (fps):

30 fps at 1920x1080; 30 fps at 1280x1024

Minimum illumination:

Color : 0.01Lux @(F1.2,AGC ON), 0.028Lux @(F2.0,AGC ON)
B/W : 0.001Lux @(F1.2,AGC ON), 0.0028Lux @(F2.0,AGC ON)

Environment

Operating Temperature (°C):

Operating: -30 °C – 60 °C

Operating Humidity (Non-condensing):

Operating: 10% ~ 90%

Installation:

Ceiling Mount with vandal resistant IK10-rated

Physical Specifications

Dimensions (W x D x H mm):

99.9 x 97.5 x 46.5 mm

Weight (g):

400 g

Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF

Environmental Test:

Weather proof IP66-rated housing
Vandal Resistant IK10-rated

Others:

Manufactured in ISO-9001 and ISO-14001 certified factory

Others

Supported Browsers:

Internet Explorer 6 or above

Order Information

FCS-3073

Package Contents

FCS-3073

Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)



Optional Accessory



CAS-7303

Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7307

Corner Mount Bracket



CAS-7321

In-ceiling Mount Bracket



CAS-7322

Wall Mount Bracket



CAS-7323

Wall Mount Bracket with Junction Box



CAS-7324

Pendant Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.