




FCS-5056 Version: 1

! Power supply unit is to be ordered separately.

HUBBLE Fixed IP Network Camera, 3-Megapixel, 802.3af PoE, IR LEDs, Vandalproof, Indoor/Outdoor



1. Ethernet Port



2. Memory Card Slot
3. Reset Button
4. Power LED

Key Features

- Built-in Micro SDHC/SDXC card slot for local storage
- Weatherproof IP68-rated housing
- 3-Megapixel high-definition resolution
-
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Built-in infrared LEDs for night viewing up to 30m
- Video compression: H.264, MJPEG
- Removable IR-cut filter for day and night surveillance
- Power support: PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license



Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3af Power over Ethernet (PoE)
TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

Image Sensor:

3-Megapixel 1/3.2" Progressive Scan CMOS

Lens:

Fixed focal, Fixed iris, Fixed focus, f4.2mm, F1.8

Port:

1 x RJ-45 10/100 Mbps PoE Port
1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

15 IR LEDs for illumination up to 30m

Shutter Time:

1/5 ~ 1/10,000 sec

Angle of View:

62.7°

Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

Video Compression:

H.264 / MJPEG

Resolution:

3M (2048x1536)

Output Video Format:

RAW

Power Input:

802.3af PoE

Power Consumption:

PoE Class 2 (IEEE802.3af) / 3.36 W (IR on)

Data Rate:

10/100Mbps

Storage Capacity:

SD/MicroSD memory card of up to 64GB

Features

Video:

Image Setting: - Adjustable image size, quality and bit rate
- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR), Basic WDR (74 dB)
- 2D Noise Reduction (2DNR)

Streaming: Up to 2 video streams

Performance

Frame Rate (fps):

15 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Minimum illumination:

Color: 0.1 lux at F1.8

B/W: 0 lux (IR LED on)

Environment

Operating Temperature (°C):

Operating: -40°C ~ 50°C

Operating Humidity (Non-condensing):

Operating: 10% ~ 85%

Installation:

Wall Mount

Physical Specifications

Dimensions (W x D x H mm):

232 x 202 x 95 mm

Weight (g):

704 g

Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF, IP68, IK10, NEMA 4X

Environmental Test:

Weather proof IP68-rated housing


Vandal proof IK10-rated

Others

Supported Browsers:

Microsoft Windows 8/7/Vista/XP

Diagram





Order Information

FCS-5056

Package Contents

FCS-5056

Wall Mount Kit

Quick Installation Guide

Resource CD (User Manual, Utility, QIG)

Optional Accessory



CAS-2504

Pole Mount Bracket, Clamping Range 3.25"-7"



CAS-3103

Wall Mount Bracket



CAS-3300

Ceiling Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.