



FCS-5093 Version: 1

! Power supply unit is to be ordered separately.

GEMINI Fixed IP Network Camera, 8-Megapixel, H.265, 802.3af PoE, IR LEDs, Indoor/Outdoor

The LevelOne FCS-5093 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 8-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5093 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 8-Megapixel high-definition resolution
- Video compression: H.264, H.265
- Built-in infrared LEDs for night viewing up to 50m
- Weatherproof IP67-rated housing
- Built-in Micro SDHC/SDXC card slot for local storage
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments

Specifications

System Specifications

Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

Image Sensor:

1/2.5" Progressive Scan CMOS

Lens:

4 mm @ F2.0

Port:

1 x RJ-45 10/100 Mbps PoE port
Power Connector
1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

Indicator:

Power

**IR Cut Filter:**

Removable infrared-cut filter for day & night function

IR LED:

IR LEDs for illumination up to 50m

Shutter Time:

1/3 ~ 100,000 sec

Angle of View:

79°

Video Compression:

H.265,H.264,H.264+,MJPEG(stream 2)

Resolution:

50Hz: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

Output Video Format:

AVI

Power Input:

12 VDC ± 25%, PoE(802.3af 42.5 – 57 V, class 3)

Power Consumption:

12 VDC ± 25%, 7.5W; PoE, 9.5W

Data Rate:

32 Kbps to 16 Mbps

Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

Wireless

Data Transfer Rate:

Video Bit Rate : 32 Kbps to 16 Mbps

Features

General:

rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser.120dB Wide Dynamic Range

PoE:

PoE(802.3at)

Security:

One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark,IP Address Filter

Management:

Behavior Analysis: Line crossing detection, intrusion detection, unattended baggage detection, object removal detection

Line Crossing Detection: Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported

Intrusion Detection: Enter and loiter in a pre-defined virtual region, up to 1 pre-defined virtual regions supported

Object Removal Detection: Objects removed from the pre-defined region, such as the exhibits on display.

Unattended Baggage Detection: Objects left over in the pre-defined region such as the baggage, purse, dangerous materials

Face Detection: Human face appears in the image can be detected and trigger linkage method.

Video:

Support 1 fixed region for mainstream and sub stream separately

Performance

Number of Clients:

32

Frame Rate (fps):

50Hz: 20 fps (3840 × 2160)

60Hz: 20 fps (3840 × 2160)

Minimum illumination:

Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR

Environment

Operating Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Operating Humidity (Non-condensing):

95% or less

Physical Specifications

Dimensions (W x D x H mm):

?104.8 × 299.7 mm (?4.13? × 11.8?)

Weight (g):

1200 g (2.65 lb.)

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Environmental Test:

IP67

Others:

ONVIF

Manufactured in ISO-9001 and ISO-14001 certified factory

RoHS

Others

Supported Browsers:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Order Information

FCS-5093

Package Contents

FCS-5093

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit



Optional Accessory



CAS-7303

Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7307

Corner Mount Bracket



CAS-7311

Junction box for Bullet Camera



CAS-7312

Power Intake Box for Bullet Camera

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.