



FCS-5211 Version: 1

GEMINI Fixed IP Network Camera, 2-Megapixel, H.265, 4.3X Optical Zoom, IR LEDs, Indoor/Outdoor

The LevelOne FCS-5211 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5211 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Supports 4.3X optical zoom
- Video compression: H.264, H.265, MJPEG
- Built-in infrared LEDs for night viewing up to 50m
- Vandal-proof IK10-rated housing
- Digital input/output (1DI/1DO) for sensor and alarm
- Power support: PoE (IEEE 802.3af)
- Supports motion detection (Intrusion/camera tampering/line crossing) and event notification

Specifications

System Specifications

Standards:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/2.8" Progressive Scan CMOS

Lens:

2.8 to 12 mm

Port:

- 1 x RJ-45 10/100 Mbps PoE port
- Power Connector
- 1 x MicroSDHC/ MicroSDXC card slot
- 1 X 1Vp 1Vp-p composite output (75 Ω/BNC)
- 1 X Terminal Block DI/DO (max 12 VDC, 30 mA)
- 1 x Audio in/Out
- 1 X Terminal Block 12 VD

**Button/Knob:**

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

IR LEDs for illumination up to 50m

Shutter Time:

1/3 s to 1/100,000 s

Angle of View:

Horizontal field of view: 105° to 35°

Vertical field of view: 56° to 20°

Diagonal field of view: 126° to 40.5°

Pan/Tilt/Zoom:

4.3X Optical Zoom

Video Format:

H.265, H.264, MJPEG(sub stream)

Resolution:

50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720)

Output Video Format:

AVI

Audio Compression:

G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM

Power Input:

12 V DC ± DC ± 25%, PoE (802.at)

Power Consumption:

12 VDC, 1.3A, max. 15.5W

PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 17.5W

Data Rate:

32 Kbps to 16 Mbps

Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

Digital Zoom:

4.3X Optical Zoom

Operating Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Operating Humidity (Non-condensing):

Humidity 95%

Features

General:

Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment, Anti-Flicker, Watermark, Privacy Mask, Automatic gain control (AGC) .

PoE:

PoE(802.3at)

Security:

One-key Reset, Heartbeat, Password Protection, IPv4, IPv6, File Management, Object Removal Detection, IP address filtering.

Management:

Event Triggers (Network Disconnected, IP address Conflict, Illegal Login, HDD Full, HDD Error, Alarm Input, Alarm Output, Line Crossing Detection, Intrusion Detection, Face detection)

Video:

120dB Wide Dynamic Range, BLC, Auto White Balance (AWB), Privacy Mask (up to 5 region), 3D DNR, Triple Stream

Audio:

8kHz/16kHz/32kHz/44.1kHz/48kHz

Performance

Number of Clients:

32

Frame Rate (fps):

Main Stream (H.265/H.264)

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 39fps (1920 × 1080, 1280 × 960, 1280 × 720)

Sub Stream (H.265/H.264/MJPEG)

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream (H.265/H.264)

50Hz: 25fps (1920 × 1080, 1280 × 720, 640 × 360, 352 × 288)

60Hz: 30fps (1920 × 1080, 1280 × 720, 640 × 360, 352 × 240)

Minimum illumination:

Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR

B/W: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR

Physical Specifications

Dimensions (W x D x H mm):

144.13 x 144.13 x 332.73

Weight (g):

1893 g (4.171 b.)

Color:

White

Approval and Compliance

EMI/EMS:

CE, FCC, UL

Safety:

IK10

Environmental Test:

IP67

Others:

Manufactured in ISO-9001 and ISO-14001 certified factory

RoHS

ONVIF, ISAPI.

Others



Supported Browsers:

Plug-in required live view: IE8+, Chrome 41.0-44, Firefox 30.0-51, Safari 8.0-11

Plug-in free live view: Chrome 45.0+, Firefox 52.0+

Order Information

FCS-5211

Package Contents

FCS-5211

Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.