

USB Print Server

H/W Version: 2

Product Overview

The LevelOne FPS-1032 print server is an ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing over the same network. This print server is equipped with a 10/100Mbps autosensing Ethernet port and a USB 2.0 port that connected to USB printer.

Multi OS and Network Printing Protocol Support

The FPS-1032 1-port USB print server supports Windows ME/NT/2000/XP/2003/Vista and Win7 operating systems as well as Mac OS 8.1 and higher, UNIX/Linux and Netware (Bindery/NDS). Network Protocol supported includes TCP/IP, IPX, NetBEUI,



FPS-1032

AppleTalk, LPR, RAW TCP and SMB over TCP/IP for flexible use with different network clients connected to the same office network. The FPS-1032 also includes Internet Printing Protocol (IPP) support and Windows Print Monitor Technology to monitor printing jobs received.

Easy Installation Wizard

The LevelOne FPS-1032 is easily configurable using a Web Browser or Windows based configuration program included with the CD-ROM. The print server is easily managed through a Web based user interface and the firmware is upgradeable through TFTP, the windows set-up program or the Web based user interface.



1. Power Port 2. LED Indicators 3. Reset Button



4. RJ-45 LAN Port 5. USB Port 6. Wall-Mountable

Key Features

- USB print server for network print sharing
- High-speed USB 2.0 interface
- Fast Ethernet network connectivity
- Easy set-up wizard included
- Web based user interface
- Support multiple operating systems
- Support multiple network printing protocols

Related Products



FPS-1031 Print Server with 1 Parallel Port



FPS-1033 Print Server with 2 USB and 1 Parallel Ports

Technical Specification

Device Specifications	Device Management
Standards Compliance	Web-based user interface
IEEE 802.3, 802.3u Ethernet Standards	Windows-based Setup Program
Network Interface	SNMP & HP Web JetAdmin Support
1x 10/100Mbps Auto-sensing RJ-45 port	Physical Specifications
1x USB 2.0 Auto-sensing port	LEDs
DHCP Client	Power/Status, Link, Activity
Operating System Support	Power Supply
Windows ME/NT/2000/XP/2003/ Vista/	5V, 2A
7/8/8.1/10 Mac OS 8.1 or higher	Dimension
UNIX/Linux	73.16mm (L) x 64.75mm (W) x 28.39mm (H)
NetWare (Bindery/NDS)	Weight
Network Print Protocol Support	58g
TCP/IP, IPX, NetBEUI, AppleTalk, LPR, RAW TCP, SMB over TCP/	Operating Temperature and Humidity
IP,Internet Printing Protocol (IPP)	Operating: 0°C ~ 50°C @ 0% ~ 70% (non-condensing)
Software Upgradeable	Storage: -5°C ~ 65°C @ 0%~ 80% (non-condensing)
Web interface	EMI Certifications
Windows-based Setup Program	CE, FCC Class B
TFTP	

Product Diagram

Internet Wireless Broadband Router Ureless Broadband Bouter Ureless Broadband Bouter<

Printer

Order Information Package Content

FPS-1032: USB Print Server

FPS-1032 Power Adapter Quick Installation Guide CD Manual/QIG/Utility

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.