

## 24-Port Gigabit Ethernet Switch



H/W Version: 2

## **Gigabit Speed**

GSW-2457 is a 24-port Gigabit Ethernet Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 1000 Mbps. Increase the speed of your network backbone to a massive 48Gbps and bring Gigabit speeds all the way to your computers.

#### **Control Your Network**

With an 8K MAC address table, the GSW-2457 has no problems remembering where to send the data packets. Also featuring IEEE 802.3x flow control and

IEEE 802.1p Quality of Service functions so you have greater control over your networks. The switch also supports Auto MDI/MDI-X cable detection on all ports to eliminate the need for crossover or Uplink ports for an easy plug-and-play installation.

#### **Rack Mountable**

This 19 inch rack mountable switch with internal power is ideal for the professional office environment.





- 1. Power LED
- 2. LAN Port LEDs
- 3. LAN Ports
- 4. Internal power socket

#### **Key Features**

- 24-Port Combo Ethernet Switch for highperformance office networks
- Large 48Gbps Switch bandwidth
- Supports Auto-negotiation and Auto-MDI/MDI-X on all ports
- Support 802.1p QoS
- Store-and-Forward switching architecture
- Compiles with 802.3, 802.3u and 802.3ab standards
- Wire-speed packet filtering and forwarding
- 8K MAC Address and 512KB buffer memory
- 19-inch Rack-Mountable

#### **Works Well With**



#### **GNC-0105T** 32-bit Gigabit Ethernet PCI Adapter



# USB-0201 USB Gigabit Ethernet Adapter

#### **Technical Specifications**

#### **Network Interface**

## **Standard Compliance**

IEEE 802.3 10-BASE-T Ethernet
IEEE 802.3u 100-BASE-TX
IEEE 802.3ab 1000-BASE-T
IEEE 802.3x Flow Control

IEEE 802.1p QoS

#### Interface

24 x 10/100/1000Mbps Auto-negotiation, Auto-MDIX ports

#### **Protocol**

CSMA/CD

#### **Switching Method**

Store-and-Forward switching architecture

#### **MAC Address Table**

8K

#### Jambo Frame

10KB

## Buffer

512KB

#### **LED**

Power, Link/ Act, 1000Mbps

## **Power Supply**

100-240V ~50/60Hz, 0.6A

#### **Power Consumption**

18.6W

## **Operating Environment**

Temperature: 0 to 40°C

Humidity: 10% ~ 90% (Non-condensing)

Storage: -40°C ~ 70°C


## Dimensions (L x W x H)

440mm x 180mm x 44mm

### **EMI and Safety**

CE/FCC ClassA

### **Product Diagram**



Order Information

**GSW-2457:** 24-Port Gigabit Ethernet Switch

**Package Contents** 

GSW-2457 Power Cord

Rack-Mount Kit

User Manual