



IEC-1200

10/100 Industrial Media Converter w/ 15.4W PoE PSE, SC MM 2KM -10 to 60C

Overview

LevelOne IEC-1200 is an industrial Fast Ethernet media converter with IP30 ingress protection case. This converter is designed to be mounted on an industrial standard DIN-rail, plus the clearly visible status LEDs provide simple monitoring of port link activity.

Power over Ethernet

This converter is Power Sourcing Equipment (PSE), and it is fully compliant with IEEE 802.3af PoE standard at maximum 15.4W power budget per port. It helps to save infrastructure wiring costs dramatically by eliminating electric wiring and less UPS needed.

Cost Effective

This device operates under -10 to 60 Celsius (-14 to 140 Fahrenheit) temperature that offers optimal suitability for industrial applications at low cost while maintaining all components built to withstand harsh environment applications without compromise reliability and stability.

Plug & Play


This Industrial Media Converter is designed for the demanding industrial environments at businesses in need of instant connectivity with no setup or configure required, truly plug and play.

Features

- Provides 1-port 10/100Base-TX plus 1-port 100Base-FX
- 100Base-FX Multi-mode fiber for the link up to 2 kilometers
- IEEE802.3af PoE PSE with 15.4W power budget
- 10/100Mbps Full/Half duplex, Auto-negotiation, Auto-MDI/MDIX
- Complies with IEC61000-6-2 EMC Generic standard immunity for industrial environment
- 228K bits buffer memory
- -10°C to 60°C (14°F to 140°F) and is tested for functional operation @ -20°C to 70°C (-4°F to 158°F)
- IP30 aluminum case
- Supports DIN-rail mounting installation

Diagrams

Unit: mm



Specifications

Technology	
Standards	<ul style="list-style-type: none"> IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX/FX
Forward and Filtering Rate	<ul style="list-style-type: none"> 14,880pps for 10Mbps 148,810pps for 100Mbps
Packet Buffer Memory	<ul style="list-style-type: none"> 228K bits
Processing Type	<ul style="list-style-type: none"> Store-and-Forward Half-duplex back-pressure and IEEE802.3x full-duplex flow control

Power	
Input	<ul style="list-style-type: none"> Input Voltage: 48VDC
Power Consumption	<ul style="list-style-type: none"> 3.6W Max. 0.075A @ 48VDC 19.2W Max. 0.4A @ 48VDC when PoE link with 15.4W IEEE802.3af PD
Overload Current Protection	<ul style="list-style-type: none"> Present
Reverse Polarity Protection	<ul style="list-style-type: none"> Present

Mechanical	
Casing	<ul style="list-style-type: none"> Aluminum case IP30
Dimensions	<ul style="list-style-type: none"> 70mm (W) x 110mm (D) x 30mm (H) (2.76" (W) x 4.33" (D) x 1.18" (H))
Weight	<ul style="list-style-type: none"> 0.25Kg (0.55lb.)
Installation	<ul style="list-style-type: none"> DIN-Rail (Top hat type 35mm)

Interface	
Ethernet Port	<ul style="list-style-type: none"> 10/100BASE-TX: 1 port 100BASE-FX: 1 port
LED Indicators	<ul style="list-style-type: none"> Per Unit: Power Status (Power) Per Port: 10/100TX: Link/Activity, Full-duplex/Collision, 100FX: Link/Activity PoE: PD connect/PD disconnect

Environment	
Operating Temperature	<ul style="list-style-type: none"> -10°C to 60°C (14°F to 140°F) Test @ -20°C to 70°C (-4°F to 158°F)
Storage Temperature	<ul style="list-style-type: none"> -40°C to 85°C (-40°F to 185°F)
Ambient Relative Humidity	<ul style="list-style-type: none"> 5% to 95% (non-condensing)
MTBF	<ul style="list-style-type: none"> 47.37 years

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> Manufactured in an ISO9001 facility
Safety	<ul style="list-style-type: none"> UL508
EMI	<ul style="list-style-type: none"> FCC Part 15, Class A EN61000-6-4 <ul style="list-style-type: none"> EN55022 EN61000-3-2 EN61000-3-3
EMS	<ul style="list-style-type: none"> EN61000-6-2 <ul style="list-style-type: none"> EN61000-4-2 (ESD Standards) Contact: + / - 4KV Air: + / - 8KV EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM EN61000-4-4 (Burst Standards) Signal Ports: + / - 4KV D.C. Power Ports: + / - 4KV EN61000-4-5 (Surge Standards) Signal Ports: + / - 1KV; Line-to-Line D.C. Power Ports: + / - 0.5KV; Line-to-earth EN61000-4-6 (Induced RFI Standards) Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz
Environmental Test Compliance	<ul style="list-style-type: none"> IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) FED STD 101C Method 5007.1 (Free fall w/ package) -Tested with Cross Weight and Drop High standard table

Order Information

IEC-1200 - 10/100 Industrial Media Converter w/ 15.4W PoE PSE, SC MM 2KM -10 to 60C

Package Contents

IEC-1200

Quick Installation Guide