

# 8-port Combo KVM Switch w/ Expansion Slot

# H/W Version: 2

The LevelOne KVM-0831 8-port combo KVM switch enables users to control and manage several computers or even an entire server farm, using a single keyboard, mouse and monitor. Users can switch to different servers using hot-keys or push button for fast control of the connected devices.


Up to 120 computers can be connected to KVM-0831 using a daisy chain. This gives network administrator the ability to control large groups of servers or systems from one console without the need to physically move between different monitoring stations.

# Advanced Remote Management via optional modules

LevelOne also offers a unique module for remote server control. Just slide in the IP Console Module (ACC-2000) to KVM-0831/1631 to access and manage the server farm over the Internet using a standard web browser. It supports a 1600x1200 pixel screen resolution for high-quality viewing.

KVM-0831

LevelOne also has a module (ACC-1000) that allows system administrators to extend the control over the LAN using Cat.5 cabling to control servers and PCs remotely up to 300 meters away.



#### **Key Features**

- Control servers and computers either locally via control port or remotely via optional modules through the module expansion slot
- Features an expansion slot for flexible installation with optional module choices
- Locate Cat5 console up to 300 meters away from the KVM switch.
- To enable/disable the Screen Saving function and 10 min auto-logout function.
- High video display quality up to 1920x1440
- Support Windows, NetWare, Unix, Linux, Mac OS and Sun Microsystems
- Firmware Upgradable

#### **Works Well With**



ACC-1000 KVM Cat.5 Console Module




KVM-9007 KVM Cat.5 Receiver

### **Technical Specifications**

| Console Port                      | Rack-Mounted            |
|-----------------------------------|-------------------------|
| USB x 2, VGA x 1                  | 19" industry-standard   |
| PC Port                           | Scan interval           |
| (PS2/USB/VGA) Combo connector x 8 | 5~99 sec                |
| Cascade Control PC no.            | Resolution              |
| 120                               | 1920 x 1440             |
| Cable Model Name                  | Dimension (mm)          |
| ACC-2001 ACC-2002                 | 445(H)) x 160(W) x45(H) |
| Applicable to Computer            | Size                    |
| PS2/USB                           | 1U                      |
| OSD                               | Power Supply            |
| Yes                               | DC 12V, 1A              |
| Pushbutton Control                | Operation Temp.         |
| Yes                               | Operating: 0~50°C       |
| LEDs                              | Storage Temp.           |
| 8                                 | -20°C ~ 60°C            |
| Hot plug and Play                 | Humidity                |
| Yes                               | 0~95%, Non-Condensing   |
| Hotkey Control                    | System MTBF             |
| Yes                               | MTBF: 75138.181         |

## **Product Diagram**



Order Information Package Contents **KVM-0831:** 8-port Combo KVM Switch w/ Expansion Slot

KVM0831, Power Adapter DC 12V, 1.0A, Rack Mount Kit, Rubber Feet, User Manual

## **Option Accessories**



ACC-2109 Daisy Chain Cable 90cm



ACC-2101 PS/2 and USB Cable KVM 1.8m ACC-2102 PS/2 and USB Cable KVM 3.0m



ACC-2103 PS/2 and USB Cable KVM 5.0m

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright Digital Data Communications GmbH. All Rights Reserved.