

# 11a(5.500~5.825Ghz) 10dBi Omni-Directional Antenna

## **OAN-4101**

**LevelOne's** OAN-4101 10dBi omni-directional outdoor antenna is an ideal solution to increase wireless signal coverage and improve signal strength/quality for existing 802.11a wireless devices in the range between 5.5Ghz to 5.825Ghz frequency bands.

This antenna is especially designed for outdoor applications such as the WAB-7400 outdoor access point. The waterproof surface keeps the antenna workable in any rogue environment. In order to increase installation flexibility there is no power-source required.

The antenna can be easily fastened on a wall or installed on a pole. OAN-4101 has been tested for interoperating with LevelOne's wireless access point, WAB-2000A mesh outdoor AP/Bridge. This unit can also work with other wireless devices, which comply with IEEE802.11a standard and are equipped with an N male connector.



- For IEEE 802.11a applications at the range between 5.5GHz to 5.825GHz frequency band
- Easy to install
- Omni-directional operation provides extended point to multi-point coverage



Related Products



11a/b/g Outdoor PoE Wireless AP WAB-7000



11a/b/g/g Outdoor Mesh PoE Wireless AP

WAB-7400

## **Product Diagram**




OAN-4101 works with WAB-7400 for Mesh Network or Point-to-Multipoint bridging applications

# 11a(5.500~5.825Ghz) 10dBi Omni-Directional Antenna

## **OAN-4101**

## **Technical Specifications**



V-Plane Co-polarization Pattern

## **Electrical Specification**

### Frequency Band

5.GHz-5.825GHz

Gain

10dBi

**VSWR** 

2.0:1 Max

**Polarization** 

Linear, Vertical

HPBW/V

7°

HPBW/H

360°

**Downtilt** 

2°

**Power Handling** 

5W

Impedance

50 Ohms


Connector

N female

## **Package Contents**

[1] OAN-4101

[2] Wall & Pole Mounting



**H-Plane Co-polarization Pattern** 

#### **Environmental & Mechanical Characteristics**

### Survival wind speed

216m/hr

#### **Temperature**

**-4**0°C **-** + 80°C

#### Humidity

95% @ 55° C

#### **Radome Material**

Fiber Glass, UV resistant

## Weight

265g

#### **Dimension**

80mm x 780mm x511mm

# **Optional Accessories**

ANC-4230 400 Series N plug to N plug Cable 3m

ANC-2210 200 Series N plug to N plug Cable 1m

ANC-2310 200 Series N plug to RPSMA plug Cable 1m

ANA-6100 6GHz Outdoor Arrestor

# **Ordering Information**

OAN-4101, 11a (5.500~5.825 Ghz) 10dBi Omni-Directional Antenna