

200Mbps HomePlug AV Adapter

H/W Version: 2

Product Overview


PLI-2040 200Mbps HomePlug AV Adapter is a high definition cost-effective Ethernet adapter which allows home and office users to build a speedy data network over existing electrical wiring. It is ideal for users that have two different workgroups that are located in different parts of the home.

Utilizing the home power line infrastructure

Transmit data using the existing electrical wiring in your building by simply plug PLI-2040 into an AC outlet. This is a fast, simple, and cost-effective alternative to installing expansive Ethernet cables throughout your entire home or small office. For this purpose PLI-2040 x 2 starter kit is also available for a quick set-up of a home network*.

Built-in QoS for fast network speeds





delivering high quality multimedia streams over the

PLI-2040 HomePlug AV is featured with Quality of Service (QoS) which ensures sufficient bandwidth for

PLI-2040

Up to 10 times faster than other HomePlug devices when store, transfer and access large files to LevelOne's Network Attached Storage (NAS), such as FNS-1020 and GNS-2000.

128-bit AES secure encryption for enhance network protection and data transmission.

* PLI-2040 starter kit is available which includes 2 HomePlugs, a user's manual, a utility CD for quick installation and a quick started guide.

- 1. Reset Button
- 2. Security Push Button
- 3. RJ-45 Ethernet Port
- 4. LED Indicators
- 5. Power Plug

Key Features

- Stream HD (High Definition) multimedia content across your home network
- Built-in QoS Engine for prioritized audio and video streaming

1 2 3

- Provides up to 200Mbps data transfer rate
- 128-bit AES secure encryption for enhanced network protection
- Simple Plug-and-Play Installation
- Cost-effective network solution
- Deliver the benefits of Ethernet without wiring expense
- Power Packet Utility provides unsophisticated users a way to graphically manage their HomePlug network

Works Well With



PLI-3110 HomePlug Pro PoE



FNS-1020 1-Bay Simple Network Storage (H/W: 2.0)

Technical Specification

Computer Interface

IEEE802.3; IEEE802.3u

Standards

HomePlug AV

Network Interface

One RJ-45 (10/100Base-T Ethernet)

Security

128-bit AES Link Encryption with Key Management

Software

HomePlug Configuration Tool for Microsoft Windows 98 SE, ME, 2000, XP, and 32-bit Vista, 7

Data Transfer Rate

200 Mbps over Powerline and 10/100Mbps over Ethernet

Modulation Schemes

OFDM Symbol Modulation on Line synchronization 1024/256/64/16/8 - QAM, QPSK, BPSK, ROBO Carrier Modulation

Frequency Band

2 ~ 28 Mhz

Additional Protocols

Mix of TDMA and CSMA/CA channel access scheme;CO device generates a periodic beacon carrier for channel access scheme

Operation Range

Estimated range of 300m in wall power lines

Cabling

100Base-T; Cat. 5 UTP Cable

Operating Temperature

0°C to 40°C ambient temperature

Storage Temperature

-20°C to 70°C ambient temperature

Humidity

10 to 90% maximum (non-condensing)

Power Input

100 ~ 240V @ 50/60Hz Internal

Housing

Plastic (96mm x 70mm x 32mm)

Software Utility

Device Detect/Diagnostic, NEK Password Setup for Local and Remote Device Windows 2000, ME, NT, XP, or Vista, 7 for Initial Setup


LED

PL – Link/Act; Traffic–Link/Act; ETH – Link/Act

Certifications

HomePlug AV PowerLine Specification FCC Class B / CE Mark / HomePlug Certification

Product Diagram



Order Information PLI-2040: 200Mbps HomePlug AV Adapter

PLI-2040: 200Mbps HomePlug AV Adapter Starter Kit

Package Contents PLI-2040

Quick Installation Guide RJ-45 Ethernet LAN Cable Quick Installation Guide CD Manual / Utility