





POW-1210

36W 12VDC Industrial Power Adapter, DC Plug -40 to 75C

The POW-1210 industrial power adapter is featuring built-in surge protection, universal input voltage range and full compliance with all important safety and EMC standards. It can be operated at full load across an ambient temperature range of -40 to 75 Celsius degree without need of additional cooling to guarantee quality for harsh industrial environment.

Features

- Universal AC Input at Full Range
- Output equipped with DC Plug
- Short Circuit, Overload / Over Voltage Protection
- Slim & Lightweight Design
- 100% Full Load Burn-in Test

Diagrams

Unit: mm

28 35"+2 0"
(720 0:50)

GREEN LED

18 35"
(120 0)

GREEN LED

18 35"
(120 0)

GREEN LED

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)

18 35"
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120 0)
(120

Specifications

Output DC	12V	Dimension & Weight	115 x 53 x 38mm @ 0.28kg
Output Current	3.0A	Operation Temperature	-40 to 75 Celsius
Output Power	36W	Operation Humidity	0 to 90% RH Non-condensing
Input Voltage	90-264VAC		EN60950-1, UL60950-1, EN55011, EN55022 (CISPR22) Class B, EN61000-3-2, EN61000-3-3, EN61000-4-2/3/4/5/6/8/11,
MTBF	34.20 years		
			EN61000-6-2, EN61204, EN55024

Order Information

POW-1210 - 36W 12VDC Industrial Power Adapter, DC Plug -40 to 75C

Package Contents

POW-1210 with DC Plug