



## 2-Megapixel Day/Night Wireless P/T Network Camera



WCS-6020

H/W Version: 1

The LevelOne WCS-6020 is a quality yet cost-effective surveillance solution for the home and office. It is designed for easy and flexible installation, provides a choice of either a 150Mbps wireless or wired connection and a WPS (Wi-Fi protected setup) button to secure the wireless connection with just the push of a button, and the motorized Pan and Tilt provides a viewing angle of  $\pm 355^\circ$  pan and  $\pm 135^\circ$  tilt. Equipped with a 2-Megapixel sensor and built-in IR cut filter/IR illuminator LEDs, the camera provides high resolution quality and sharp sensitivity – ideal for security applications both day and night.

The WCS-6020 is equipped with many advanced features such as Level1DNS™ Service, DI/DO for external alarm and sensor, a SD/SDHC card slot and USB interface for local storage, built-in microphone and external speaker for 2-way audio communications. Moreover, users can also set up 16 motion-detection regions with the camera, each with adjustable size and sensitivity. When motion is detected at the specified regions, the system can send an E-mail alert or send captured images via FTP upload to a designated storage server. The WCS-6020 is indisputably the top choice for reliable and high performance surveillance.

### Remote Viewing Made Easy

Level1DNS™ service, an intelligent dynamic DNS service which is handy at situation where IP address of your LevelOne device is not permanent, which is frequently changed by your ISP. By offering you an unique domain name, our Level1DNS™ service ensures your device is always reachable from anywhere around the globe and easy remote access through web browsers.

### 64-channel Management Software

We aim to offer you the most versatile and comprehensive surveillance solutions. Our IP CamSecure software coming with the camera allows you to monitor up to 64 megapixel IP cameras simultaneously on one screen to enhance scalability. For added convenience and flexibility, the software includes various advanced features such as scheduling recording, event alert, and heaps more. In addition, simply install our free iCamSecure App to your smartphone and connect to the PC with IP CamSecure software installed, you will easily turn your iPhone/Android smartphone into a portable surveillance system for real-time monitoring and snapshot.

### Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Compatible with IEEE 802.11b/g/n wireless standards
- Built-in infrared LEDs for night viewing up to 10m
- Supports 355° pan and 135° tilt
- Compression: H.264/MPEG-4/MJPEG
- Supports 2 video streams simultaneously
- Simple wireless connectivity and security with WPS push button
- Removable IR-cut filter for day and night surveillance
- Built-in microphone and external speaker for 2-way audio communication
- Digital input/output (1DI/1DO) for sensor and alarm
- Built-in SD/SDHC card slot for local storage
- Supports motion detection and event notification via e-mail or FTP
- Free 64-channel monitoring software included (supports iCamSecure App)

### Works Well With



**WBR-6003**  
150Mbps Wireless Router



**GNS-1001**  
1-Bay Gigabit Network Storage

## Technical Specification


<b>Camera</b>
<b>Image Sensor</b> 2-Megapixel 1/2.7" Progressive Scan CMOS
<b>Effective Pixels</b> 1920x1080
<b>Lens</b> Board lens, fixed-focal, f=4.0 mm, F2.0
<b>Angle of View (H)</b> 62°
<b>Minimum Illumination</b> Color: 1.5 lux at F2.0 B/W: 1.0 lux at F2.0
<b>IR Cut Filter</b> Removable infrared-cut filter for day & night function
<b>Shutter Time</b> 1 to 1/10000 sec.
<b>Pan/Tilt/Zoom</b> Pan range: ±355°(-177.5°~177.5°) Tilt range: ±135° (-45°~ 90°) Auto pan mode Auto patrol mode
<b>IR LED</b> 12 IR LEDs for illumination up to 10m
<b>Video</b>
<b>Video Compression</b> H.264 / MPEG4 / MJPEG
<b>Resolutions</b> 1080p(1920x1080) / SXGA(1280x1024) / WXGA(1280x800) / VGA(640x480) / QVGA(320x240) / QCIF(176x144)
<b>Frame Rate</b> Up to 30 fps at 1920x1080
<b>Video Streaming</b> Multiple simultaneous streams, up to 2 streams
<b>Image Setting</b> - Adjustable image size, quality and bit rate - Configurable brightness, sharpness, contrast, saturation, white balance and exposure - AGC/AWB/AES - Flip & Mirror - Time Stamp
<b>Video Format</b> AVI
<b>Audio</b>
<b>Audio Streaming</b> 2-way audio
<b>Audio Compression</b> G.726 / AMR
<b>Audio Input/Output</b> Built-in microphone Mic/line input, line output
<b>Network</b>
<b>Networking</b> 10/100 Mbps Ethernet, RJ-45 Built-in 802.11b/g/n WLAN
<b>Security</b> Multi-level user access with password protection IP address filtering
<b>Supported protocols</b> TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP, Samba
<b>Number of clients</b> 20
<b>DNS</b> Easy Internet monitoring via configuration free Level1DNS™ service

<b>Wireless</b>
<b>Networking</b> Built-in 802.11b/g/n WLAN
<b>Transfer Rate</b> 802.11n: 6.5~72.2/13.5~150Mbps 802.11g: 54 ~ 6 Mbps 802.11b: 11 ~ 1 Mbps
<b>Wireless Security</b> WEP, WPA-PSK, WPA2-PSK
<b>Channels</b> Ch.1 ~ 11 USA Ch.1 ~ 13 EU
<b>Operating Frequency</b> 2.412 ~ 2.472GHz
<b>Antenna</b> 2x 2dBi antennas
<b>Alarm and Event Management</b>
<b>Motion Detection</b> 16 Detection Zones
<b>Notification</b> FTP, SMTP, Samba
<b>DI/DO</b> 1 D/I and 1 D/O for external sensor and alarm
<b>General</b>
<b>Local storage</b> SD/SDHC card slot, USB slot
<b>Power</b> DC12V 1.5A
<b>Power Consumption (Max.)</b> 12W
<b>Connectors</b> RJ-45 10BASE-T/100BASE-TX 3.5mm line out 3.5mm mic/line in WPS Button I/O terminal block (DI/DO) DC Power Jack
<b>LED Indicator</b> Power/Link
<b>Button</b> Reset Button
<b>Operating Temperature (°C)</b> 0°C ~ 40°C
<b>Operating Humidity (Non-condensing)</b> 10% to 80%
<b>Dimensions</b> 105 x 105 x 110 mm
<b>Weight</b> 356 g
<b>Approvals</b> CE, FCC
<b>Viewing System Requirements</b> OS: Microsoft Windows 7/Vista/XP Browser: Internet Explorer 6.x or above, Firefox, Chrome, Safari Cell phone: 3GPP player Real Player: 10.5 or above Quick Time 6.5 or above
<b>Bundled Software</b> Bundled with 64-Channel LevelOne IP CamSecure surveillance management software

## Front View and Rear View



## Product Diagram



## Order Information

### Package Contents

**WCS-6020:** 2-Megapixel Day/Night Wireless P/T Network Camera

WCS-6020, Antenna x 2, Power Adapter, Camera Stand, Quick Installation Guide, CD Manual / Utility

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright Digital Data Communications GmbH. All Rights Reserved.