



11g 54 Mbps Dongle USB Adapter



WNC-0301USB


H/W Version: 3

LevelOne's WNC-0301USB is a wireless USB dongle adapter that is fully compliant with IEEE 802.11g to deliver data rates up to 54 Mbps at 2.4 GHz. This device provides reliable wireless data communication to help extend your network's capabilities.

The device supports UPnP standard, you can easily and quickly install the adapter into any desktop or notebook with the setup wizard and the hot-swappable USB interface. Like LevelOne's other wireless adapters,

WNC-0301USB can be used in the infrastructure mode by connecting the wireless AP or router to the internet seamlessly or in Ad-hoc mode to connect with other wireless computers for file sharing.

WNC-0301USB follows wireless security standards 64/128 WEP, WPA-TKIP, and AES encryption and is further enhanced with 802.1x user authentication. With a compact and portable design, the device makes it an easy fit for any limited space.



1. USB Port
2. Power/Link LED

Key Features

- Complies with the IEEE 802.11b and IEEE 802.11g 2.4GHz (DSSS) standards
- High data transfer rate up to 54Mbps
- Supports 64/128-bit WEP, WPA (PSK, TKIP with IEEE 802.1x), WPA2 (PSK, AES with IEEE 802.1x) functions for high level of security. (WPA2 for Windows 2000/XP only)
- Supports the most popular operating system Windows 98SE/ME/2000/XP
- Supports USB 2.0/1.1/1.0 interface
- Portable and mini-size design

Works Well With



WAP-3100
11g Wireless PoE AP



WBR-3408
54Mbps Wireless Router w/ QoS


Technical Specification

Standards
IEEE 802.11g, IEEE 802.11b
Host Interface
USB Port Type: USB 2.0, 1.1, 1.0
Radio Operation
Data Transfer Rate
802.11g: 54, 48, 36, 24, 18, 12, 9 and 6 Mbps
802.11b: 11, 5.5, 2 and 1 Mbps
Modulation
802.11g: OFDM
802.11b: CCK, QPSK, BPSK
Media Access Control
CSMA/CA with ACK
Frequency Band
2.4GHz ~ 2.4835GHz
Number of Channels
Channel 1~11 North America
Channel 1~13 Europe, Japan
Receiver Sensitivity (Typical)
802.11g: -70 dBm @ 54Mbps
802.11b: -83.5 dBm @ 11Mbps
Transmitter Output Power (Typical)
802.11g/b: 17 ± 2dBm


Network Security
- WEP-64/128 bit
- WPA
- WPA-PSK
- WPA2
- WPA2-PSK
-TKIP, AES with 802.1x
Device Management
Windows Utility Software
OS Supported: Windows 98SE/ME/2000/XP
Physical Specifications
LED
Power/Link
Temperature
Operating: 0°C ~ 50°C
Humidity
0% ~ 95% (non-condensing)
Dimensions
87mm(D) x 27mm(W) x 9mm(H)
Certifications
CE,FCC

Product Diagram

Infrastructure Mode



Ad-hoc Mode



Order Information

WNC-0301USB : 11g 54 Mbps Dongle USB Adapter

Package Contents

WNC-0301USB

USB Cable

Quick Installation Guide

CD Manual/Driver/Utility

Option Accessories



SUS-1000
Small USB Stand



SUS-1003
Small USB Stand
with extension cable