

# 11g Wireless USB Adapter



#### **Product Overview**

The LevelOne WUA-0315 is a wireless USB adapter for delivering high-speed wireless connectivity to notebook or desktop computers that do not have built-in wireless support. It is fully compliant with IEEE 802.11g for fast and stable throughput and is backward compatible to 802.11b for legacy device integration.

## **Easy Installation**

The device supports UPnP standard, you can easily and quickly install the adapter into any desktop or notebook with the built-in installation wizard and the hot-swappable USB



WUA-0315

2.0/1.1/1.0 interface. WUA-0315 is compatible with Windows 2000, XP and Vista. With a compact and portable design, it is an easy fit for users that want to minimize the clutter around their computers.

# **Advanced Security Encryption**

The LevelOne WUA-0315 supports 64/128-bit WEP Key wireless data encryption as well as standard WPA security. For advanced industry standard encryption, the WUA-0315 provides further support for WPA2 encryption for enhanced security and user authentication.



1. USB Port 2. Power/Link LED

#### **Key Features**

- Compatible with IEEE 802.11b and IEEE 802.11g standards
- Enjoy high-speed Wireless connectivity through your USB port
- Easy Plug-and-Play setup with installation wizard
- Supports 64/128-bit WEP ,WPA and WPA2 encryption with 802.1x support for high level security
- Portable and mini-size design
- Windows configuration for Wi-Fi Protected Setup (WPS)
- Supports Window 2000/XP/Vista

#### **Works Well With**



WBR-3408 54Mbps Wireless Router w/ QoS




WBR-3600 11g Wireless ADSL2+ Router

## **Technical Specification**

Standards	Device Management
	Device Management Windows Utility Software
IEEE 802.11g, IEEE 802.11b Host Interface	
	OS Supported: Windows 2000/XP/Vista 32bit/ Vista 64bit
USB Port Type: USB 2.0, 1.1, 1.0	Physical Specifications
Radio Operation	
Data Transfer Rate	Power/Link
802.11g: 6 ~ 54 Mbps	Temperature
802.11b: 1 ~ 11 Mbps	Operating: 0°C ~ 40°C
Modulation	Storage: -20°C ~ 70°C
802.11g: OFDM	Humidity
802.11b: CCK, QPSK, BPSK	5% ~ 90% (non-condensing)
Media Access Control	Power Requirement
CSMA/CA with ACK	DC 5V ± 5%
Frequency Band	Dimensions
2.4GHz ~ 2.4835GHz	54.8(L) x 21.4(W) x 7.8 mm(H)
Number of Channels	Certifications
Channel 1 ~ 11 North America	CE,FCC
Channel 1 ~ 13 Europe, Japan	
Transmitter Output Power (Typical)	
802.11g: 13.5 ± 1 dBm	
802.11b: 17 ± 1 dBm	
Network Security	
- WEP-64/128 bit	
- WPA	
- WPA-PSK	
- WPA2	
- WPA2-PSK	
- 802.1x RADIUS	
- Support WPS configuration	

# **Product Diagram**



Order Information Package Contents WUA-0315: 11g Wireless USB Adapter

WUA-0315 Quick Installation Guide CD Manual/Driver/Utility

#### **Optional Accessories**



**SUS-1000** Small USB Stand



**SUS-1003** Small USB Stand with extension cable

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright 2008 Digital Data Communications GmbH. All Rights Reserved.